

Prototype reimplementations of L^AT_EX 2 _{ε} 's block environments using templates

L^AT_EX Project*

v0.9a 2025-01-20

Abstract

Contents

1	Introduction	3
2	Object types and templates for blocks and lists	3
2.1	Object types	3
2.1.1	The object type ‘block’	3
2.1.2	The object type ‘para’	3
2.1.3	The object type ‘list’	4
2.1.4	The object type ‘item’	4
2.1.5	The object type ‘blockenv’	4
2.2	Templates	4
2.2.1	The <code>blockenv</code> template ‘display’	4
2.2.2	The <code>block</code> template ‘display’	6
2.2.3	The <code>para</code> template ‘std’	6
2.2.4	The <code>list</code> template ‘std’	7
2.2.5	The <code>item</code> template ‘std’	7
3	Tagging support	8
3.1	Paragraph tags	8
3.2	Tagging recipes	10
4	Debugging	11
5	New and redefined kernel command	11

*Initial reimplementations of lists done by Bruno Le Floch, generalized second version with tagging support by Frank Mittelbach.

6	The Implementation	12
6.1	Handling \par after the end of the list	12
6.2	Object and template interfaces	14
6.3	Useful helper commands	15
6.3.1	Debugging	16
6.4	Implementation of templates	17
6.4.1	Implementation of blockenv templates	17
6.4.2	Implementation of para templates	22
6.4.3	Implementation of block templates	22
6.4.4	Implementation of list templates	25
6.4.5	Implementation of \item template(s)	28
6.5	Tagging support commands	35
6.5.1	List tags	40
6.6	Tagging recipes	42
7	Implementation of document-level block environments	44
7.1	Displayblock environments	45
7.2	The center, flushleft, and flushright environments	45
7.3	Display quote environments	45
7.4	Verbatim environments	45
7.4.1	Helper commands for verbatim	46
7.5	Standard list environments	47
7.6	verse environment	47
7.7	Theorem-like environments	49
8	Instance declarations for environments	51
8.1	Blockenv instances	51
8.1.1	Basic instances	52
8.1.2	Center, flushleft, and flushright instances	52
8.1.3	Blockquote instances	53
8.1.4	The theorem instance	54
8.1.5	The verbatim instance	54
8.1.6	Standard list instances	55
8.2	Block instances	56
8.2.1	Displayblock instances	56
8.2.2	Verbatim instances	57
8.2.3	Quote/quotationblock instances	57
8.2.4	Block instances for the theorems	57
8.2.5	Block instances for the standard lists	58
8.3	List instances for the standard lists	58
8.4	Item instances	59
8.5	Para instances	59
A	Documentation from first prototype implementations	61
A.1	Open questions	61
A.2	Code cleanup	61
A.3	Tasks	61
B	Plan of attack of first prototype	62

1 Introduction

The list implementation in L^AT_EX 2_< serves a dual purpose: it implements real lists such as `itemize` or `enumerate`, but it is also used as the basis for vertical blocks, i.e., to specify the vertical spacing and paragraph handling after such block, e.g., in environments like `center`, `quote`, `verbatim`, or in the theorem environments. They are all implemented as “trivial” lists with a single (hidden) item.

While this was convenient to get a consistent layout using a single implementation it is not adequate if it comes to interpreting the structure of a document, because environments based on `trivlist` should not advertise themselves as being a “list” — after all, from a semantic point of view they aren’t lists.

The approach taking here is therefore to offer separate object types: `block` (horizontally or vertically oriented data that needs some handling at the start and the end), `para` (that deals with different paragraph layouts), `list` (that handles list related parameters, and `item` (for item layouts and handling), to address the independent aspects and also offer the object type `blockenv` that ties them together as necessary.

For example, a `quote` environment would make use of a (display) `block` and some `para` handling while an standard `enumerate` would make use of a display `block`, a `list`, and an `item` and `para` instance. An inline list (like `enumerate*` from the `enumitem` package) would be using the same `list` instance but a different (horizontally oriented) `block`.

2 Object types and templates for blocks and lists

2.1 Object types

2.1.1 The object type ‘block’

Arg: 1 key/value list to alter the default block parameters

Semantics:

Handle the layout aspects of a block of data. In case of a “display” block (i.e., vertically oriented) the spacing and page breaking as well as the handling if the block starts a paragraph or ends one, that is, if text is immediately following the block without being separated by an empty line, then this text is considered to be in the same paragraph as the block.

In case of a horizontally oriented block it covers any special handling at the start and end of the block, e.g, extra spacing, prohibiting or encouraging line breaks, and so forth.

2.1.2 The object type ‘para’

Arg: 1 key/value list to alter the default item parameters

Semantics:

Sets up paragraph-specific parameters for H&J, e.g., to implement justification variations, the behavior of \\ etc. The instances are used in higher-level templates, e.g., in a *block*.

2.1.3 The object type ‘list’

Arg: 1 key/value list to alter the default item parameters

Semantics:

Handle the aspects related to list design, e.g., the use and formatting of counters, etc.

Note that this does not cover block-related aspects, i.e., a list instance could be used both for a display list or for an inline line.

2.1.4 The object type ‘item’

Arg: 1 key/value list to alter the default item parameters

Semantics:

A sub-type used as part of *list* to easily cover alternative layout for list items.

2.1.5 The object type ‘blockenv’

Arg: 1 key/value list to alter the default item parameters

Semantics:

This object type is used to implement document-level environments. It defines a *block* instance to handle the layout at the “edge” of the environment data, possibly some paragraph setup through a *para* instance, potentially an “inner” instance for more complicated environments (such as lists), and possibly some additional setup code for certain environments.

It also defines how the *blockenv* behaves with respect to nesting, e.g., does it change when nested and if so how many levels of nesting are supported, etc.

Finally, the object type defines how it appears in a tagged PDF document, what tag names are used, how they are rolemapped and whether it adds additional attributes, etc.

2.2 Templates

2.2.1 The `blockenv` template ‘display’

Attributes:

env-name (*tokenlist*) Name of the environment used in tracing and error messages

tag-name (*tokenlist*) Name of the tag in the PDF. If not explicitly given the name is defined by the `tagging-recipe`

tag-class (*tokenlist*) An explicit tag class attribute

tagging-recipe (*tokenlist*) Defines the way tagging is done. Currently the values `basic`, `standard`, and `list` are supported Default: `standard`

level-increase (*boolean*) Does this `blockenv` increase the block level if it is nested in an outer block? Default: `true`

setup-code (*tokenlist*) Initial setup code. This is executed after legacy defaults (from `\@listi`, `\@listii`, etc.) are used but before the block instance is called

block-instance (*tokenlist*) Part of the name of the `block` instance that is called. The full name has a `-<level>` appended Default: `displayblock`

para-instance (*tokenlist*)

inner-level-counter (*tokenlist*) Name of an existing (!) counter that is incremented and used to determine final name of the `inner-instance` or empty if always the same inner instance should be used

max-inner-levels (*tokenlist*) Maximum number of nested environments of this kind. Only relevant if there is a `inner-level-counter` specified Default: 4

inner-instance-type (*tokenlist*) Object type of the inner instance Default: `list`

inner-instance (*tokenlist*) Name of the inner instance (if any).

para-flattened (*boolean*) `describe` Default: `false`

final-code (*tokenlist*) Final setup code Default: `\ignorespaces`

Semantics & Comments: This `blockenv` template supports the legacy list setting that are found in many document classes in the macros `\@listi`, `\@listii`, up to `\@listvi`. It also uses the counter `\@listdepth` to track nesting of block, again mainly to support legacy setups (internally it gives it a more appropriate name but it remains accessible through the L^AT_EX 2_< name).

It first checks that nothing is too deeply nested. If the level should increase then the increments the `\@listdepth` counter and calls the corresponding `\@list... macro` to update the legacy defaults. If `level-increase` is set to false this is bypassed.

It then sets up the tagging via the `tagging-recipe` setting and executes any code in `setup-code`.

Afterwards it calls the appropriate `block` instance based on `block-instance` and current level, e.g., `displayblock-1`. Then it sets up paragraph parameters if a `para-instance` was specified (otherwise they stay as they are).

If a `inner-instance` was specified this is called next, or more precisely: if no `inner-level-counter` was specified the instance `inner-instance` is called.

Otherwise, the `inner-level-counter` is incremented and the instance with the name `inner-instance-inner-level-counter` is called.

Finally, the `final-code` is executed (by default `\ignorespaces`).

The maximum number of `blockenvs` that can be nested into each other is restricted by the L^AT_EX counter `maxblocklevels` with a default value of 6. If this value is increased then it is necessary to provide additional instances, e.g., `displayblock-7`, etc. Decreasing is, of course, always possible, then some of the instances defined are not used and instead the user gets an error that there is too much nesting going on.

If the key `level-increase` is set to `false` then such an environment doesn't alter the nesting level and therefore you can nest those environments as often as you like (a typical example would be `flushleft` anywhere in the nesting hierarchy, that would have no effect on hitting the boundary).

2.2.2 The block template ‘display’

Attributes:

`heading` (*tokenlist*) *not really used yet*

`beginsep` (*skip*) Default: `\topsep`

`begin-par-skip` (*skip*) Default: `\partopsep`

`par-skip` (*skip*) Default: `\parsep`

`end-skip` (*skip*) Default: value from `beginsep`

`end-par-skip` (*skip*) Default: value from `begin-par-skip`

`item-skip` (*skip*) The space in front of an item if the block is a list; if not the setting has no effect Default: `\itemsep`

`beginpenalty` (*integer*) Default: `\@beginparpenalty`

`endpenalty` (*integer*) Default: `\@endparpenalty`

`leftmargin` (*length*) Default: `\leftmargin`

`rightmargin` (*length*) Default: `\rightmargin`

`parindent` (*length*) Default: `0pt`

Semantics & Comments: The idea of a `heading` key needs some further thoughts. Maybe instead the object type should accept a second argument and receive input for such a heading from the document level instead.

The names of the keys need further thoughts and some decision. Right now it is a mixture of those with hyphens and those that match legacy register names (the way `enumitem` did its keys).

Also `parindent` conflicts with `indent-width`!

2.2.3 The para template ‘std’

Attributes:

<code>indent-width</code> (<i>length</i>)	Default: \parindent
<code>start-skip</code> (<i>skip</i>)	Default: 0pt
<code>left-skip</code> (<i>skip</i>)	Default: 0pt
<code>right-skip</code> (<i>skip</i>)	Default: 0pt
<code>end-skip</code> (<i>skip</i>)	Default: \flushglue
<code>fixed-word-spaces</code> (<i>boolean</i>)	Default: false
<code>final-hyphen-demerits</code> (<i>integer</i>)	Default: 5000
<code>cr-cmd</code> (<i>tokenlist</i>)	Default: \normalcr
<code>para-class</code> (<i>tokenlist</i>)	Default: justify

2.2.4 The list template ‘std’

Attributes:

<code>counter</code> (<i>tokenlist</i>)	Counter name to be used in a numbered list or empty, if the list is unnumbered
<code>item-label</code> (<i>tokenlist</i>)	Label “string” for a fixed label or as generated from the current counter value
<code>start</code> (<i>integer</i>)	Start value for the counter if the list is numbered, otherwise irrelevant Default: 1
<code>resume</code> (<i>boolean</i>)	Should a numbered list be resumed from the last instance? Default: false
<code>item-instance</code> (<i>instance</i>)	Instance of type <code>item</code> to be used to format the label string Default: basic
<code>item-skip</code> (<i>skip</i>)	The space in front of an item in the list. If not specified the value specified in the block template instance is used
<code>item-indent</code> (<i>length</i>)	Horizontal displacement of the item. Default: 0pt
<code>item-penalty</code> (<i>integer</i>)	Penalty for breaking before an item (except the first) Default: \itempenalty
<code>label-width</code> (<i>length</i>)	Width reserved for the formatted item label Default: \labelwidth
<code>label-sep</code> (<i>length</i>)	Horizontal separation between label and following text Default: \labelsep
<code>legacy-support</code> (<i>boolean</i>)	Is formatting the label via <code>\makelabel</code> supported? Default: false

2.2.5 The `item` template ‘std’

Attributes:

<code>counter-label</code> (<i>function1</i>) <i>unused</i>	Default: \arabic{#1}
<code>counter-ref</code> (<i>function1</i>) <i>unused</i>	Default: value from <code>counter-label</code>
<code>label-ref</code> (<i>function1</i>) <i>unused</i>	Default: #1
<code>label-autoref</code> (<i>function1</i>) <i>unused</i>	Default: <code>item</code> #1
<code>label-format</code> (<i>function1</i>) Formatting of the label, questionable the way it is used	Default: #1
<code>label-strut</code> (<i>boolean</i>) Add a <code>\strut</code> to the label?	Default: false
<code>label-align</code> (<i>choice</i>) Supported values <code>left</code> , <code>center</code> , <code>right</code> , and <code>parleft</code> . <i>Only partly implemented</i>	Default: right
<code>label-boxed</code> (<i>boolean</i>) Should the label be boxed?	Default: true
<code>next-line</code> (<i>boolean</i>)	Default: false
<code>text-font</code> (<i>tokenlist</i>) <i>unused</i>	
<code>compatibility</code> (<i>boolean</i>)	Default: true

Semantics & Comments: This template is only rudimentary implemented at the moment. It probably needs other keys and the existing ones need a proper implementation.

3 Tagging support

3.1 Paragraph tags

Paragraphs in L^AT_EX can be nested, e.g., you can have a paragraph containing a display quote, which in turn consists of more than one (sub)paragraph, followed by some more text which all belongs to the same outer paragraph.

In the PDF model and in the HTML model that is not supported — a limitation that conflicts with real live, given that such constructs are quite normal in spoken and written language.

The approach we take to resolve this is to model such “big” paragraphs with a structure named `<text-unit>` and use `<text>` (rollmapped to `<P>`) only for (portions of) the actual paragraph text in a way that the `<text>`s are not nested. As a result we have for a simple paragraph the structures

```
<text-unit>
  <text>
    The paragraph text ...
  </text>
</text-unit>
```

The `<text-unit>` structure is rollmapped to `<Part>` or possibly to `<Div>` so we get a valid PDF, but processors who care can identify the complete paragraphs by looking for `<text-unit>` tags.

In the case of an element, such as a display quote or a display list inside the paragraph, we then have

```

<text-unit>
  <text>
    The paragraph text before the display element ...
  </text>
  <display element structure>
    Content of the display structure possibly involving inner <text-unit> tags
  </display element structure>
  <text>
    ... continuing the outer paragraph text
  </text>
</text-unit>

```

In other words such a display block is always embedded in a `<text-unit>` structure, possibly preceded by a `<text>...</text>` block and possibly followed by one, though both such blocks are optional.

Thus an `itemize` environment that has some introductory text but no text immediately following the list would be tagged as follows:

```

<text-unit>
  <text>
    The intro text for the itemize environment ...
  </text>
  <itemize>
    <LI>
      <Lbl> label </Lbl>
      <LBody>
        The text of the first item involving <text-unit> as necessary ...
      </LBody>
    </LI>
    <LI>
      The second item ...
    </LI>
    ... further items ...
  </itemize>
</text-unit>

```

The `<itemize>` is rollmapped to `<L>`.

For some display blocks, such as centered text, we use a simpler strategy. Such blocks still ensure that they are inside a `<text-unit>` structure but their body uses simple `<text>` blocks and not `<text-unit><text>` inside, e.g., the input

```

This is a paragraph with some
\begin{center}
  centered lines
with a paragraph break between them

```

```
\end{center}
followed by some more text.
```

will be tagged as follows:

```
<text-unit>
  <text>
    This is a paragraph with some
  </text>
  <text /0 /Layout /TextAlign/Center>
    centered lines
  </text>
  <text /0 /Layout /TextAlign/Center>
    with a paragraph break between them
  </text>
  <text>
    followed by some more text.
</text-unit>
```

3.2 Tagging recipes

There are a number of different tagging recipes that implement different tagging approaches. They are selected through the `tagging-recipe` of the `blockenv` template. Currently the following values are implemented:

standalone This recipe does the following:

- Ensure that the `blockenv` is not inside a `<text-unit><text>` structure. If necessary, close the open one (and any open `<text>` structure).
- Text inside the body of the environment start with `<text-unit><text>` unless the key `para-flattened` is set to `true` (which is most likely the wrong thing to do because we then get just `<text>` as the structure).
- At the end of the environment close `</text>` and possibly an inner `</text-unit>` if open.
- Finally, ensure that after the environment a new `<text-unit>` is started, if appropriate, e.g., if text is following.

basic This recipe does the following:

- Ensure that the `blockenv` is inside a `<text-unit>` structure, if necessary, start one.
- If inside a `<text-unit><text>`, then close the `</text>` but leave the `<text-unit>` open.
- Text inside the body of the environment start with `<text-unit><text>` if `para-flattened` is set to `false`, otherwise just with `<text>`.
- At the end of the environment close `</text>` and possibly an inner `</text-unit>` if open.
- Then look if the environment is followed by an empty line (`\par`). If so, close the outer `<text-unit>` and start any following text with `<text-unit><text>`. Otherwise, don't and following text restarts with a just a `<text>` (and no paragraph indentation)

standard This recipe is like the **basic** one as far as handling `<text-unit>` and `<text>` is concerned. In addition

- it starts an inner tagging structure (i.e., which is therefore a child of the outer `<text-unit>`).
- By default this structure is a `<Figure>` unless overwritten by the key `tag-name`. If that key is used, a suitable rollmap needs to be provided for the name given.
- At the end of the environment that inner structure is closed again so that we are back on the `<text-unit>` level from the outside.
- Then the lookahead for an empty line is done as described previously.

list This recipe is like the **standard** one except that

- the inner structure is a list (`<L>`).
- Furthermore everything is set up so that we have list items (``) with suitable substructures (`<Lbl>` for the item labels and `<LBody>` for the item bodies).
- If the key `tag-name` is specified, this is used as the tag name for the whole list instead of `<L>`. Of course, it should then have a suitable rollmap.
- If the key `tag-class` is specified then this is used as the class attribute. Again, this requires a suitable setup on the outside.
- At the end of the environment the `</LBody>`, ``, and `</L>` (or the tag name used) are closed.
- Then the lookahead for an empty line is done as described previously.

4 Debugging

```
\DebugBlocksOn  
\DebugBlocksOff  
\block_debug_on:  
\block_debug_off:
```

These commands enable/disable debugging messages.

5 New and redefined kernel command

```
\@doendpe
```

The original L^AT_EX 2 _{ε} command is augmented to allow for tagging.

```
\legacyverbatimsetup  
\legacylistsetupcode
```

```
\@setupverbinspace
```

A counterpart definition to the kernel command `\@setupverbinspace`, needed as we need to handle real space chars in verbatim.

`endblockenv` *to be documented*
`\g_block_nesting_depth_int`

`\newtheorem` Redefined to make theorems tagging aware.
`\@thm`
`\@begintheorem`

`\item` The `\item` is redefined.
`\@itemlabel`

`\c@maxblocklevels` A counter to increase or decrease the number of supported level. If increased, one needs to supply additional level instances.

`\begin` The `\begin` is slightly redefine to handle `\@doendpe` better. TODO: move to kernel

`\para_end:` TODO: consider name, document

`\para/begin` The para/begin hook is enhanced to support list ends

6 The Implementation

```
1  {*package}
2  {@@=block}
3  \ProvidesPackage {latex-lab-testphase-block}
4      [\ltlabblockdate\space v\ltlabblockversion\space
5       blockenv implementation]
6
7  General kernel changes, also loaded by the sec and toc code.
6  \RequirePackage{latex-lab-kernel-changes}
7  \ExplSyntaxOn
```

6.1 Handling `\par` after the end of the list

An empty line (or a `\par`) after a list has semantic meaning as it defines whether the following text is logically within the same paragraph as the list (no empty line) or whether it starts a new paragraph and the paragraph containing the list ends at the end of the list (empty line after the list). This is handled by L^AT_EX using a legacy flag called `@endpe` and set of commands inside the generic `\end` (calling `\@doendpe`) and as part of the list environments identifying themselves as “paragraph ending environments” (by setting this flag).

For the reimplementations of the list environments including support of tagging we need to augment that mechanism slightly and add some kernel hook(s) to add the tagging code if needed.

\@doendpe The original L^AT_EX 2_< command is augmented to allow for tagging. TODO: use sockets for this and move to the kernel eventually.

```
8 \def\@doendpe{\@endpetrue
9   \def\par
10  {
```

If we are processing a \$\$ math display and we encounter a real `\par` after it, we need to add a `\parskip` when tagging is done, because the one added by TeX is always canceled by the processing in `__math_tag_dollardollar_display_end`: in that case. This is signaled by the global legacy switch `@domathendpe` which is set to true in that case. Once the skip is applied we set it to false. If there is no `\par` at all, it will be reset in `\everypar` when the next paragraph starts.

```
11   \if@domathendpe
12 %       \typeout{----->~ add~ another~ parskip~ that~ is~
13 %                           not~ canceled:~ \the\parskip }
14     \skip_vertical:n { \tex_parskip:D }
15     \@domathendpefalse
16   \fi
17   \restorepar
18   \clubpenalty\clubpenalty
```

At this point we add the tagging code that closes an open `<text-unit>, <text>` tag combination, if necessary:

```
19 \__kernel_displayblock_doendpe:
```

The standard `\par` command (`\par_end:`) acts on `@endpe` and attempts to close a still open `<text-unit>`s and this would be wrong if it was already closed above. So we have to reset the switch to false first.

```
20   \@endpefalse
21   \everypar{}
22   \par
23  }
24   \everypar{{\setbox\z@\lastbox}
25     \everypar{}
26     \@endpefalse
```

Not sure what is faster: testing for the status of the switch or setting it unconditionally to false (globally), probably roughly the same, so we set it always:

```
27 %           \if@domathendpe
28 %               \@domathendpefalse
29 %           \fi
30 }
31 }
```

By default we don't do any tagging:

```
32 \cs_new_eq:NN \__kernel_displayblock_doendpe: \prg_do_nothing:
```

(End of definition for `\@doendpe` and `__kernel_displayblock_doendpe`. This function is documented on page ??.)

`\if@domathendpe` Signal that special paragraph handling after a math display is required.
`\@domathendpefalse`
`\@domathendpetrue`

```
33 \newif\if@domathendpe
34 \def\@domathendpefalse{\global\let\if@domathendpe\iffalse}
35 \def\@domathendpetrue {\global\let\if@domathendpe\iftrue}
```

(End of definition for `\if@domathendpe`, `\@domathendpefalse`, and `\@domathendpetrue`. These functions are documented on page ??.)

6.2 Object and template interfaces

blockenv (objecttype) All object types expect a single key–value argument used to tweak template parameters
block (objecttype) specific to a given use in the document. This section is devoted to template interfaces,
para (objecttype) and the template code is covered later.

```

36 \NewTemplateType{blockenv}{1}
37 \NewTemplateType{block}{1}
38 \NewTemplateType{para}{1}
39 \NewTemplateType{list}{1}
40 \NewTemplateType{item}{1}
```

blockenv display (templ.)

```

41 \DeclareTemplateInterface{blockenv}{display}{1}
42 {
43   env-name      : tokenlist ,
44   tag-name      : tokenlist ,
45   tag-class     : tokenlist ,
46   tagging-recipe : tokenlist = standard,
47   level-increase : boolean = true ,
48   setup-code    : tokenlist ,
49   block-instance : tokenlist = displayblock ,
50   para-instance  : tokenlist ,
51   inner-level-counter : tokenlist,
52   max-inner-levels   : tokenlist = 4,
53   inner-instance-type : tokenlist = list ,
54   inner-instance   : tokenlist ,
55   para-flattened : boolean = false ,
56   final-code     : tokenlist = \ignorespaces ,
57 }
```

block display (templ.)

```

58 \DeclareTemplateInterface{block}{display}{1}
59 {
60   heading      : tokenlist = ,           % ??
61   beginsep     : skip = \topsep ,
62   begin-par-skip : skip = \partopsep ,
63   par-skip     : skip = \parsep ,
64   end-skip     : skip = \KeyValue{beginsep} , % conflict with name below
65   end-par-skip : skip = \KeyValue{begin-par-skip} ,
66   item-skip    : skip = \itemsep ,
67   beginpenalty : integer = \UserName{@beginparpenalty} ,
68   endpenalty   : integer = \UserName{@endparpenalty} ,
69   leftmargin   : length = \leftmargin ,
70   rightmargin  : length = \rightmargin ,
71   parindent    : length = Opt ,
72   % maybe add? (or more general for fonts and color)
73   % font        : tokenlist
74 }
```

para std (templ.)

```

75 \DeclareTemplateInterface{para}{std}{1}
76 {
77   para-class      : tokenlist = justify ,
78   indent-width    : length = \parindent ,
```

```

79   start-skip          : skip = Opt ,
80   left-skip           : skip = Opt ,
81   right-skip          : skip = Opt ,
82   end-skip            : skip = \@flushglue ,
83   fixed-word-spaces   : boolean = false ,
84   final-hyphen-demerits : integer = 5000 ,
85   cr-cmd              : tokenlist = \@normalcr ,
86 }
87
list std (templ.)
88 \DeclareTemplateInterface{list}{std}{1}      % optional
89 {
90   counter           : tokenlist = ,
91   item-label         : tokenlist = ,
92   start              : integer = 1 ,
93   resume             : boolean = false ,
94   item-instance      : instance{item} = basic ,
95   item-skip          : skip = \itemsep ,
96   item-penalty       : integer = \UseName{@itempenalty} ,
97   item-indent        : length = \itemindent ,
98   label-width        : length = \labelwidth ,
99   label-sep          : length = \labelsep ,
100  legacy-support     : boolean = false ,
101
item std (templ.)
102 \DeclareTemplateInterface{item}{std}{1}
103 {
104   counter-label     : function{1} = \arabic{#1} ,
105   counter-ref        : function{1} = \KeyValue{counter-label} ,
106   label-ref          : function{1} = #1 ,
107   label-autoref     : function{1} = item-#1 ,
108   label-format       : function{1} = #1 ,
109   label-strut         : boolean = false ,
110   label-align        : choice {left,center,right,parleft} = right ,
111   label-boxed        : boolean = true ,
112   next-line          : boolean = false ,
113   text-font          : tokenlist ,
114   compatibility       : boolean = true ,
115

```

6.3 Useful helper commands

This section collects `\exp3` commands that will be useful.

`__block_skip_set_to_last:N` Set a skip register to the value of an immediately preceding skip or zero if there was none.
`__block_skip_remove_last:`

```

115 \cs_new_protected:Npn \__block_skip_set_to_last:N #1 {
116   \skip_set:Nn #1 f \tex_lastskip:D }
117 }
```

Remove a skip previous skip if it is directly in front (not allowed in unrestricted vertical mode).

```

118 \cs_new_eq:NN \__block_skip_remove_last: \tex_unskip:D
```

(End of definition for `_block_skip_set_to_last:N` and `_block_skip_remove_last:..`)

119 `\cs_generate_variant:Nn \tl_if_no_value:nTF { o }`

6.3.1 Debugging

`\g_block_debug_bool`

120 `\bool_new:N \g_block_debug_bool`

(End of definition for `\g_block_debug_bool.`)

`_block_debug:n`

121 `\cs_new_eq:NN _block_debug:n \use_none:n`

122 `\cs_new_eq:NN _block_debug_typeout:n \use_none:n`

(End of definition for `_block_debug:n` and `_block_debug_typeout:n.`)

`\block_debug_on:`

`\block_debug_off:`

`_block_debug_gset:`

123 `\cs_new_protected:Npn \block_debug_on:`

124 `{`

125 `\bool_gset_true:N \g_block_debug_bool`

126 `__block_debug_gset:`

127 `}`

128 `\cs_new_protected:Npn \block_debug_off:`

129 `{`

130 `\bool_gset_false:N \g_block_debug_bool`

131 `__block_debug_gset:`

132 `}`

133 `\cs_new_protected:Npn __block_debug_gset:`

134 `{`

135 `\cs_gset_protected:Npx __block_debug:n ##1`

136 `{ \bool_if:NT \g_block_debug_bool {##1} }`

137 `\cs_gset_protected:Npx __block_debug_typeout:n ##1`

138 `{ \bool_if:NT \g_block_debug_bool { \typeout{==>~ ##1} } }`

139 `}`

(End of definition for `\block_debug_on:`, `\block_debug_off:`, and `__block_debug_gset:.` These functions are documented on page 11.)

`\DebugBlocksOn`

`\DebugBlocksOff`

140 `\cs_new_protected:Npn \DebugBlocksOn { \block_debug_on: }`

141 `\cs_new_protected:Npn \DebugBlocksOff { \block_debug_off: }`

142 `\DebugBlocksOff`

(End of definition for `\DebugBlocksOn` and `\DebugBlocksOff`. These functions are documented on page 11.)

6.4 Implementation of templates

6.4.1 Implementation of blockenv templates ...

`\g_block_nesting_depth_int`

L^AT_EX 2_< already has a counter to record the nesting depth of blocks, but we want our own name because it isn't really tied to "lists" any more. However, `\@listdepth` is really part of the legacy interface (for example `minipage` alters it to point to a different counter) so that we are stuck with using at least indirectly for now and the following line makes this look like an L3 integer variable but internally expands to `\@listdepth`:

```
143 \cs_new:Npn \g_block_nesting_depth_int { \@listdepth } % a fake int
144 % for now
```

(End of definition for `\g_block_nesting_depth_int`. This function is documented on page 11.)

`blockenv display (templ.)`

```
145 \DeclareTemplateCode{blockenv}{display}{1}
146 {
147   env-name      = \l__block_env_name_tl ,
148   tag-name      = \l__block_tag_name_tl ,
149   tag-class     = \l__block_tag_class_tl ,
150   tagging-recipe = \l__block_tagging_recipe_tl ,
151   level-increase = \l__block_level_incr_bool ,
152   setup-code    = \l__block_setup_code_tl ,
153   block-instance = \l__block_block_instance_tl ,
154   para-instance  = \l__block_para_instance_tl ,
155   para-flattened = \l__tag_para_flattened_bool ,
156   inner-level-counter = \l__block_inner_level_counter_tl ,
157   max-inner-levels  = \l__block_max_inner_levels_tl ,
158   inner-instance-type = \l__block_inner_instance_type_tl ,
159   inner-instance   = \l__block_inner_instance_tl ,
160   final-code     = \l__block_final_code_tl ,
161 }
162 {
163   \__block_debug_typeout:n{\l__block_env_name_tl -env-start}
164 %
165   \SetKnownTemplateKeys{blockenv}{display}{#1}
```

We need to know later if we have nested blockenvs inside a flattened environment. Whenever we start a new blockenv we increment `\l__tag_block_flattened_level_int` if it is already different from zero. If it is zero we increment it if flattening is requested. Thus a value of 0 means no flattening requested so far and 1 means this is the first blockenv requesting flattening. In either case we have to make sure that the blockenv is surrounded by a `<text-unit>` tag, while for any value above 1 we have to omit the `<text-unit>`.

```
166 \int_compare:nNnTF \l__tag_block_flattened_level_int > 0
167 {
168   \int_incr:N \l__tag_block_flattened_level_int
169 }
170 {
171   \bool_if:NT \l__tag_para_flattened_bool
172   {
173     \int_incr:N \l__tag_block_flattened_level_int
174   }
175 }
176 %
```

```

177   \tl_if_empty:NF \l__block_inner_level_counter_tl
178   {
179     \int_compare:nNnTF \l__block_inner_level_counter_tl >
180       { \l__block_max_inner_levels_tl - 1 }
181     { \c@toodeep }
182     { \int_incr:N \l__block_inner_level_counter_tl } % not clean "o"?
183   }

```

Legacy defaults are only roped in if the list level changes. For display blocks that remain on the same level the current values are kept.

```

184   \bool_if:NT \l__block_level_incr_bool
185   {
186     \int_compare:nNnTF \g_block_nesting_depth_int >
187       { \c@maxblocklevels - 1 }
188     { \c@toodeep }
189     {
190       \int_gincr:N \g_block_nesting_depth_int

```

If there are no legacy defaults for that level then the next line does nothing, i.e., the current values (from the last level become the defaults for the next.

```

191           \use:c { @list \int_to_roman:n
192                     { \g_block_nesting_depth_int } }
193       }
194   }

```

If we are doing tagging we load one of the available recipes for tagging, which alters various kernel hooks to add appropriate tagging structures.

```

195   \tag_if_active:T
196   { \use:c { __block_recipe_ \l__block_tagging_recipe_t1 : } }

```

The default for `list` environments is that they have an empty label and are not numbered (something that is then overwriting by the setup of a specific list). We ensure this here even for non-lists, because we need a defined state that then can be overwriting by the legacy setup code for the `list` environment in `\l__block_setup_code_t1`. This is needed in case lists are nested as they otherwise would inherit outer values (and suddenly an `itemize` would start incrementing an outer `enumerate` counter, etc.

```

197   \tl_clear:N \c@itemlabel
198   \tl_clear:N \c@listctr
199   \legacy_if_set_false:n { @nmbrlist }

```

Then run the setup code if any is given in the instance.

```

200   \l__block_setup_code_t1

```

Next call a block instance at the appropriate level passing it any key/value list provided in the optional argument (keys that are not recognized are ignored—currently with an error).

```

201   \__block_debug_typeout:n{use~ instance:~
202     \l__block_block_instance_t1 - \int_use:N \g_block_nesting_depth_int }
203   \UseInstance{block}
204     { \l__block_block_instance_t1 - \int_use:N
205       \g_block_nesting_depth_int }
206     \UnusedTemplateKeys

```

After this instance has been processed, any remaining unused keys are stored in `\UnusedTemplateKeys` and we can make use of this data later as long as we do not

call another instance that also does unused key processing and overwrites it. This is what happens below, so we better save its current value for now.

```
207  \tl_set_eq:NN \l__block_unused_blockenv_keys_tl \UnusedTemplateKeys
```

After the block instance call the para and then inner (list) instance if either or both are specified (which may not be the case).

```
208  \tl_if_empty:NF \l__block_para_instance_tl
209  {
210      \__block_debug_typeout:n{ use~ para~ instance:~ \l__block_para_instance_tl }
```

For now we don't offer to alter instance parameters here so we pass an empty argument.

```
212  \UseInstance{para}{ \l__block_para_instance_tl } {}
213 }
```

The inner instance may have its own levels or none depending on which the instance name differs. Again we pass it the optional key/value list.

```
214  \tl_if_empty:NF \l__block_inner_instance_tl
215  {
216      \__block_debug_typeout:n{use~ instance:~ \l__block_inner_instance_tl
217          \tl_if_empty:NF \l__block_inner_level_counter_tl
218              { - \int_use:N \l__block_inner_level_counter_tl } }
219      \UseInstance{ \l__block_inner_instance_type_tl }
220          { \l__block_inner_instance_tl
221              \tl_if_empty:NF \l__block_inner_level_counter_tl
222                  % not clean use "o"?
223                  { - \int_use:N \l__block_inner_level_counter_tl }
224          }
225      \l__block_unused_blockenv_keys_tl
```

Again the instance may has processed a few keys from the sofar unused keys, so we update `\l__block_unused_blockenv_keys_tl` to match the new reality.

```
226  \tl_set_eq:NN \l__block_unused_blockenv_keys_tl \UnusedTemplateKeys
227 }
```

At this point, the `\l__block_unused_blockenv_keys_tl` token list should either be empty or it should contain only keys that are suitable for the item template, but right now there is no code to test that can test the latter; it would help probably if we have an interface for this.

fix For now we handle that when the first item is encountered, but that isn't realy clean.

```
228  \tl_if_empty:NF \l__block_unused_blockenv_keys_tl
229  {
230      % check if only item template keys remain
231  }
```

We finish off with `\l__block_final_code_tl` which defaults to `\ignorespaces` so that spaces between `\begin{...}` and the start of the text are ignored.

```
232  \l__block_final_code_tl
233 }
```

`\l__block_unused_blockenv_keys_tl`

```
234 \tl_new:N \l__block_unused_blockenv_keys_tl
```

(End of definition for `\l__block_unused_blockenv_keys_tl`.)

\l__tag_block_flattened_level_int Count the levels of nested blockenvs starting with the first that is “flattened”. The counter is defined in ltagging.dtx, but until the next release 11/24 we set it up here too

```
235 \int_if_exist:NF \l__tag_block_flattened_level_int
236 {
237     \int_new:N \l__tag_block_flattened_level_int
238 }
```

(End of definition for \l__tag_block_flattened_level_int.)

\c@maxblocklevels A counter to increase or decrease the number of supported level. If increased, one needs to supply additional level instances.

```
239 \newcounter{maxblocklevels}
240 \setcounter{maxblocklevels}{6}
```

(End of definition for \c@maxblocklevels. This function is documented on page 12.)

\endblockenv The code executed when a blockenv ends is 99% the same for all blockenvs (at least up to now). Small differences exist, though. They are accounted for first in the conditionals.

We make this a public command so that new block environments can be set up without the need to resort to L3 layer programming.

```
241 \cs_new:Npn \endblockenv {
242     \__block_debug_typeout:n{blockenv~ common~ ending \on@line}
```

If this block was incrementing the level we have to decrement it now again:

```
243 \bool_if:NT \l__block_level_incr_bool
244 { \int_gdecr:N \g_block_nesting_depth_int }
```

If this block was a list and there are still \item labels to be placed we move to horizontal mode to get them typeset.

```
245 \legacy_if:nT { @inlabel }
246 {
247     \mode_leave_vertical:
248     \legacy_if_gset_false:n { @inlabel }
249 }
```

If we are ending a list environment and we have not seen any \item, i.e., @newlist is still true, we raise an error. In basic a “displayblock” scenario @newlist will always be false, but if such an environment appears inside an outer list then \noitemerr could still be triggered and that is undesirable (as the missing item will be detected at the wrong point and again later, during the outer list processing). We therefore run it only if the current environment is a list.

```
250 \__block_if_list:T { \legacy_if:nT { @newlist } { \noitemerr } }
251 \mode_if_horizontal:TF
252 { \__block_skip_remove_last: \__block_skip_remove_last: \par }
253 { \inmatherr{\end{\currenvir}} }
```

Once we are back in vertical mode we can add the appropriate closing tagging structure(s), if we are doing tagging.

```
254 \__kernel_displayblock_end:
```

Resetting the @newlist switch is also only done if the current environment is a list and not unconditionally.

```
255 \__block_if_list:T { \legacy_if_gset_false:n { @newlist } }
```

What to do in terms of vertical spacing in different situations is still somewhat open to debate, right now this is more or less implementing what L^AT_EX 2 _{ε} list environment have been doing.

some redesign/extensions here?

decide which logic we want to use! If the old logic is used we need to close the text-unit ourselves in the true branch

decide

```

256 %     \__block_debug_typeout:n{@noparlist =
257 %                               \legacy_if:nTF { @noparlist }{true}{false}}
258 \legacy_if:nF { @noparlist }
259 {
260     \__block_skip_set_to_last:N \l_tmpa_skip
261     \dim_compare:nNnT \l_tmpa_skip > \c_zero_dim
262     {
263         \skip_vertical:n { - \l_tmpa_skip }
264         \skip_vertical:n { \l_tmpa_skip + \parskip - \c_outer_pskip }
265     }
266     \addpenalty \c_endpar_penalty
267     \addvspace \l__block_topsepadd_skip

```

L^AT_EX 2 _{ε} triggered the paragraph handling after a list at this point here, i.e., only if the list didn't start a paragraph. One can make a case for that, but it can be somewhat surprising to the user and there is a good argument that even such a list could be followed explanatory text that is part of the same paragraph and doesn't start a new one.

```

268 %           \legacy_if_gset_true:n { @endpe }
269 }

```

So this is for now always done. Probably \l__block_topsepadd_skip above should be added only if the paragraph ends here and not if it continues, so this need some further cleanup.

Finally, we have a socket that handles the \par handling after the block. Normally, we use it with the `on` plug (check for a following \par) but in the case of standalone environments we assign it the `off` plug.

```

270     \socket_use:n {tagsupport/block-endpe}
271 }

```

(End of definition for \endblockenv. This function is documented on page 11.)

The following code may need some redesigning, as there is no good test for "is this environment a 'list' that has \items". For now this here does the trick well enough.

```

272 \cs_new:Npn \__block_if_list:T
273   { \tl_if_eq:NnT \l__block_block_instance_tl {list} }

```

(End of definition for __block_if_list:T.)

__kernel_displayblock_end: The kernel hook for tagging at the end of the block.

```

274 \cs_new:Npn \__kernel_displayblock_end: {
275     \__block_debug_typeout:n{\detokenize{\__kernel_displayblock_end:}}
276 }

```

(End of definition for __kernel_displayblock_end:.)

tagsupport/block-endpe (`socket`) This socket is responsible for the end environment \par handling. We define two plugs for it (`on` and `off`).

```

277 \socket_new:nn      {tagsupport/block-endpe}{0}

```

`on (plug)` The plugs set the legacy `@endpe` switch. This must always happen because block environments with different settings can be nested and should not inherit the setting from the outer environment.

```
278 \socket_new_plug:nnn{tagsupport/block-endpe}{on}
```

We can't use `\legacy_if_gset_true:n` because this is now doing more than setting the legacy switch

```
279 { \@endpetrue }
280 \socket_new_plug:nnn{tagsupport/block-endpe}{off}
281 { \@endpefalse }
282 \socket_assign_plug:nn{tagsupport/block-endpe}{on}
```

6.4.2 Implementation of para templates ...

`para std (templ.)`

```
283 \DeclareTemplateCode{para}{std}{1}
284 {
285   indent-width      = \parindent ,
286   start-skip        = \l__par_start_skip , % name??
287   left-skip         = \leftskip ,
288   right-skip        = \rightskip ,
289   end-skip          = \parfillskip ,
290   fixed-word-spaces = \l__par_fixed_word_spaces_bool , % name??
291   final-hyphen-demerits = \finalhyphendemerits ,
292   cr-cmd            = \\ ,
293   para-class         = \l__tag_para_attr_class_tl ,
294 }
295 {
296   \SetTemplateKeys{para}{std}{#1}
297   \skip_set:Nn \@rightskip \rightskip
298 }
```

6.4.3 Implementation of block templates ...

`block display (templ.)` In contrast to the L^AT_EX 2_< implementation we do not directly use `\listparindent` here but a private register of the template. The reason is that block template instances are also used outside of lists.

```
299 \DeclareTemplateCode{block}{display}{1}
300 {
301   heading          = \l__block_heading_tl ,
302   beginsep         = \topsep ,
303   begin-par-skip  = \partopsep ,
304   par-skip          = \parsep ,
305   end-skip          = \l__block_botsep_skip ,
306   end-par-skip    = \l__block_parbotsep_skip ,
307   item-skip         = \itemsep ,
308   beginpenalty     = \beginparpenalty ,
309   endpenalty        = \endparpenalty ,
310   rightmargin       = \rightmargin ,
311   leftmargin         = \leftmargin ,
312   parindent          = \l__block_parindent_dim ,
313 }
314 {
```

generalize heading usage
(or drop?)

```

315   \SetKnownTemplateKeys{block}{display}{#1}
316   \t1_if_blank:oF \l__block_heading_t1
317   { \mode_leave_vertical:
318     \textbf{\l__block_heading_t1} } % TODO customize

```

The code largely follows the logic of L^AT_EX 2_<’s `trivlist` implementation as far as it applicable for the “display block” but coded using the L3 programming layer. However, we keep all the legacy variables (e.g., `@noskipsec`) if there is some chance that they are set in classes or packages.

```

319   \legacy_if:nT { @noskipsec } { \mode_leave_vertical: }
320   \skip_set:Nn \l__block_topsepadd_skip { \topsep }
321   \mode_if_vertical:TF
322   {
323     \skip_add:Nn \l__block_topsepadd_skip { \partopsep }

```

At this point it is safe to add tagging structure(s) so we have a kernel-owned hook here for tagging. This is used to possibly start a paragraph structure (to surround the block, for example, in case of lists) and possibly do some other preparation for tagging the block.

```

324   \__kernel_displayblock_beginpar_vmode:
325   }
326   {

```

If we are in horizontal mode then the `displayblock` has to return to vertical mode now (after removing any immediately preceding skip or kern). But before we actually issue the `\par` we execute a kernel hook in which we can add tagging code. This hook is “weird” because by default it does nothing, but if tagging is wanted it takes an argument and grabs the following `\par` in order to put tagging code before and after the `\par`.

```

327   \__block_skip_remove_last: \__block_skip_remove_last:
328   \__kernel_displayblock_beginpar_hmode:w \par
329   }

```

Now we are back to legacy list implementation ...

```

330   \legacy_if:nTF { @inlabel }
331   {
332     \legacy_if_set_true:n { @noparitem }
333     \legacy_if_set_true:n { @noparlist }
334   }
335   {
336     \legacy_if:nT { @newlist } { \noitemerr }
337     \legacy_if_set_false:n { @noparlist }
338     \skip_set_eq:NN \l__block_effective_top_skip \l__block_topsepadd_skip
339   }
340   \skip_add:Nn \l__block_effective_top_skip { \parskip }

```

Next lines set some paragraph defaults, any of them may get overwritten if there is a `para-instance` specified on the `blockenv` instance.

```

341   \skip_zero:N \leftskip
342   \skip_set_eq:NN \rightskip \@rightskip
343   \skip_set_eq:NN \parfillskip \@flushglue

```

The next lines establish a parshape which is retained across paragraphs be executing `\para_end:` within a group and thus reestablishing the parshape for the next paragraph again. In case a list got started `\par` is ignored until we have seen an `\item` (or we have executed `\par` one thousand times).

```

344     \int_zero:N \par@deathcycles
345     \setpar
346     {
347         \legacy_if:nTF { @newlist }
348         {
349             \int_incr:N \par@deathcycles
350             \int_compare:nNnTF \par@deathcycles > { 1000 }
351                 { \noitemerr
352                     { \para_end: }
353                 }
354             }
355             {
356                 { \para_end: }
357             }
358         }
359     \skip_set_eq:NN \outerparskip \parskip
360     \skip_set_eq:NN \parskip \parsep

361     \dim_set_eq:NN \parindent \l_block_parindent_dim
362     \dim_add:Nn \linewidth { - \rightmargin - \leftmargin }
363     \dim_add:Nn \totallmargin { \leftmargin }
364     \tex_parshape:D 1 ~ \totallmargin \linewidth

```

This is the point where we are ready to add the tagging structure for the block, e.g., an `<L>`, a `<Figure>` or some other structure.

```
365     __kernel_displayblock_begin:
```

Finally, we have to output the vertical separation and penalty at the start of the block and make corrections for a change in `\parskip` and some other housekeeping, unless this block is inside a list and the list `\item` has not yet placed. In that case the vertical space and penalty us suppressed. This is controlled through the legacy switches `@noparitem`, `minipage`, and `@nobreak`.

```

366     \legacy_if:nTF { @noparitem }
367     {
368         \legacy_if_set_false:n { @noparitem }
369         \hbox_gset:Nn \g_block_labels_box
370         {
371             \skip_horizontal:n { - \leftmargin }
372             \hbox_unpack_drop:N \g_block_labels_box
373             \skip_horizontal:n { \leftmargin }
374         }
375         \legacy_if:nF { @minipage } % Why this chunk of code?
376         {
377             \__block_skip_set_to_last:N \l_block_tma_skip
378             \skip_vertical:n { - \l_block_tma_skip }
379             \skip_vertical:n { \l_block_tma_skip +
380                 \outerparskip - \parskip }
381         }
382     }
383     {
384         \legacy_if:nTF { @nobreak }
385             { \addvspace{\skip_eval:n{ \outerparskip - \parskip }} }
386             {
387                 \addpenalty \begin{parpenalty}

```

document 2e logic used here

```

388     \addvspace \l__block_effective_top_skip
389     \addvspace{-\parskip}
390   }
391 }
392 }
```

Extra keys to support enumitem conventions:

```

393 \keys_define:nn { template/block/display }
394 {
395   ,topsep      .skip_set:N = \topsep
396   ,partopsep   .skip_set:N = \partopsep
397   ,listparindent .skip_set:N = \listparindent
398 }
```

The internal kernel hooks for tagging.

```

399 \cs_new:Npn \__kernel_displayblock_begin: {
400   \__block_debug_typeout:n
401   {\detokenize{\__kernel_displayblock_begin:}}
402 }

403 \cs_new:Npn \__kernel_displayblock_beginpar_hmode:w {
404   \__block_debug_typeout:n
405   {\detokenize{\__kernel_displayblock_beginpar_hmode:w}}
406 }

407 \cs_new:Npn \__kernel_displayblock_beginpar_vmode: {
408   \__block_debug_typeout:n
409   {\detokenize{\__kernel_displayblock_beginpar_vmode:}}
410 }
```

(End of definition for `__kernel_displayblock_begin:`, `__kernel_displayblock_beginpar_hmode:w`, and `__kernel_displayblock_beginpar_vmode:..`)

6.4.4 Implementation of list templates ...

`\@itemlabel` Both `\@itemlabel` and `\@listctr` from the L^AT_EX 2_E list implementation are used (or set) by various packages. We therefore use them too, so that these packages have a fighting chance to work with the new tagging-aware implementation for `list`.

```

411 \tl_new:N \@itemlabel           % should have a top-level definition
412 \tl_new:N \@listctr             % should have a top-level definition
```

(End of definition for `\@itemlabel` and `\@listctr`. These functions are documented on page 12.)

`__block_evaluate_saved_user_keys:nn`

Keys set on individual list environments may be intended to alter the behavior of the template instance that defines the `\item` command. If meant to alter only a single `\item` command one would specify them in the optional argument of the `\item`, but if they should alter all items the right place would be the list environment. For this reason we need to store the values and then set them inside the `\item` template code using `\SetKnownTemplateKeys` in the appropriate context (template type and template name). This is done in `__block_evaluate_saved_user_keys:nn`. The context is provided in the two arguments (because different list environments may use different `\item` instances based on different templates. By default the command does nothing because most environments do not have user key settings.

```

413 \cs_new_eq:NN \__block_evaluate_saved_user_keys:nn \use_none:nn
```

Maybe something like this should become a public function, but for now this is a one-off for the `\item` command and therefore coded inline and internal to the block code.

```

414 \%\\cs_new:Npn \\_block_save_user_keys:n #1 {
415 %   \\tl_if_empty:nTF {#1}
416 %     { \\cs_set_eq:NN \\_block_evaluate_saved_user_keys:nn \\use_none:nn }
417 %     { \\cs_set:Npe \\_block_evaluate_saved_user_keys:nn ##1##2
418 %         { \\SetKnownTemplateKeys{##1}{##2}{ \\exp_not:n{#1} } }     }
419 %}

```

(End of definition for `_block_evaluate_saved_user_keys:nn`.)

`list std (tempL)`) This template implements numbered and unnumbered lists and can be combined with display blocks or with inline blocks.

```

420 \\DeclareTemplateCode{list}{std}{1}
421 {
422   counter      = \\l__block_counter_tl,
423   item-label   = \\l__block_item_label_tl,
424   start        = \\l__block_counter_start_int ,
425   resume       = \\l__block_resume_bool ,
426   item-instance = \\_block_item_instance:n ,
427   item-skip    = \\itemsep ,
428 %   item-par-skip = \\parsep ,
429   item-penalty  = \\@itempenalty ,
430   item-indent   = \\itemindent ,
431   label-width   = \\labelwidth ,
432   label-sep     = \\labelsep ,
433   legacy-support = \\l__block_legacy_support_bool , % FMI questionable
434 }
435 {
436   \\_block_debug_typeout:n{template:list:std}
437 %

```

We start by looking at the user supplied keys in `#1`. If there aren't any we reset `_block_evaluate_saved_user_keys:nn` to do nothing. Otherwise we evaluate and set the keys in the context of the current list template. In addition we prepare `_block_evaluate_saved_user_keys:nn` for execution in the template for `\item`.

```

438 \\tl_if_empty:oTF {#1}
439   { \\cs_set_eq:NN \\_block_evaluate_saved_user_keys:nn \\use_none:nn }
440   {
441     \\SetKnownTemplateKeys{list}{std}{#1}

```

The setup for `_block_evaluate_saved_user_keys:nn` is a bit tricky and has to be done with `\cs_set:Npe` even though we don't want to expand anything and therefore use `\exp_not:n` inside. All this does is that any `#` passed in via `#1` is doubled (e.g., from `label-format=\\fbox{#1}` which is represented as `...\\fbox{##1}`). Otherwise, we would end up with a replacement text like

```
\SetTemplateKeys {#1}{#2}{label-format=\\fbox {#1}}
```

instead of

```
\SetTemplateKeys {#1}{#2}{label-format=\\fbox {##1}}
```

resulting in very odd and puzzling behavior.

```

442      \cs_set:Npe \__block_evaluate_saved_user_keys:nn ##1##2
443      {
444          \SetKnownTemplateKeys{##1}{##2}{
445              \exp_not:o { \UnusedTemplateKeys }
446          }
447          \exp_not:n {
448              \tl_if_empty:NF \UnusedTemplateKeys
449              {
450                  \msg_error:nne { block } { unknown-keys }
451                  { \l__block_env_name_tl \space environment }
452                  \UnusedTemplateKeys
453              }
454          }
455      }

```

Has this list a counter name defined in the instance?

```

456      \tl_if_empty:NTF \l__block_counter_tl
457      {

```

If not we check if `\@nmblist` is true which may be the case in legacy environments that used `\usecounter` in the argument to the `list` environment.

```

458      \legacy_if:nT { \@nmblist }
459      {

```

In that case we only check if we should resume a previous list (`\@listctr` should be set in that case through the legacy method as well so we should be able to use it).

```

460          \bool_if:NF \l__block_resume_bool
461          {
462              \int_gset:cn{ c@ \@listctr }
463              { \l__block_counter_start_int - 1 }
464          }
465      }
466  }

```

If a counter is set in the list instance we use that one. This should be the name of a L^AT_EX counter that is already allocated externally—no runtime check is made for this: if it is not declared one will get “no such counter” error when the list is used.

```

467  {
468      \@nmblisttrue
469      \tl_set_eq:NN \@listctr \l__block_counter_tl
470      \bool_if:NF \l__block_resume_bool
471      {
472          \int_gset:cn{ c@ \@listctr }
473          { \l__block_counter_start_int - 1 }
474      }
475  }

```

Does the current instance has an item label representation? This would be possible whether or not we have a numbered list. If yes, then we use this for `\@itemlabel`, otherwise we expect that `\@itemlabel` is provided from the outside, e.g., as part of the `list` environment argument.

```

476      \tl_if_empty:NF \l__block_item_label_tl
477      {

```

```

478      \tl_set_eq:NN \citemlabel \l__block_item_label_tl
479  }

```

Finally, we signal that we are at the start of a new list (which affects how the first `\item` is handled and how `\par` commands are interpreted.

```

480 \legacy_if_gset_true:n { @newlist }

```

If we encounter horizontal material before the first `\item` we do want a `\cnoitemerr` straight away, because afterwards we end up with tagging structure faults whose cause is the missing `\item`. So we setup up `\l__block_item_everypar:` to test for this; when the first `\item` is encountered this will get reset. This is only relevant for vertical lists, when dealing with inline lists one would need to test for something else to identify that there is horizontal material between the start of the list and the first `\item` (maybe some `\spacefactor` trick could be used then, or the material is boxed first and the width is inspected as suggested by Joseph).

```

481 \cs_set_eq:NN \l__block_item_everypar: \l__block_item_everypar_first:
482 \l__block_debug_typeout:n{template:list:std~end}
483 }

```

The message that is used above when we are left with keys that are unknown:

```

484 \msg_new:nnnn { block } { unknown-keys }
485   { Some~ keys~ specified~ on~ the~ #1~ are~ unknown. }
486   {
487     The~ following~ keys~ are~ unknown~ and~ their~
488     values~ are~ ignored:\\
489     \space\space #2\\
490     Perhaps~ a~ misspelling~ or~ the~ current~ template~
491     instance~ uses~ special~ keys.
492   }

```

Extra keys to support enumitem conventions:

```

493 \keys_define:nn { template/list/std }
494 {
495   ,nosep .code:n =
496     \dim_zero:N \itemsep
497     \dim_zero:N \parsep
498     \dim_zero:N \topsep
499     \dim_zero:N \l__block_botsep_skip
500     \dim_zero:N \l__block_parbotsep_skip
501   ,midsep .skip_set:N = \topsep
502 }

```

6.4.5 Implementation of `\item` template(s)

`item std (templ.)` The item template has one hidden key `label` which is not available on the template for setting because it is only used to receive any optional data passed to the `\item` command. We therefore declare it with `\keys_define:nn` and ensure that the optional argument data to `\item` (if it is not a key/value list already) is passed to this `label` key.

```

503 \keys_define:nn { template/item/std }
504   { label .tl_set:N = \l__block_label_given_tl }
505 \DeclareTemplateCode{item}{std}{1}
506 {
507   counter-label = \l__block_counter_label:n ,
508   counter-ref = \l__block_counter_ref:n ,

```

Think about a better implementation at some point.

alignment is mostly wrong
(test short medium and
multiline labels)

next set of key not yet used

```

509     label-ref      = \__block_label_ref:n ,
510     label-autoref   = \__block_label_autoref:n ,
511     label-format    = \__block_label_format:n ,
512     label-strut     = \l__block_label_strut_bool ,
513     label-boxed     = \l__block_label_boxed_bool ,
514     next-line       = \l__block_next_line_bool ,
515     text-font       = \l__block_text_font_tl ,
516     compatibility    = \l__block_item_compatibility_bool ,

```

complete

This probably needs a different implementation (and needs completing)

```

517     label-align     = {
518         left          = \tl_set:Nn \l__block_item_align_tl { \relax \hss } ,
519         center        = \tl_set:Nn \l__block_item_align_tl { \hss \hss } ,
520         right         = \tl_set:Nn \l__block_item_align_tl { \hss \relax } ,
521         parleft       = \NOT_IMPLEMENTED ,
522     } ,
523 }

```

Then typeset the label at its natural width by applying `__block_make_label_box:n` to the label given or to a label constructed from the counter. If it is boxed and reasonably short, add padding to make it at least of size `\labelwidth`, then add another layer of box. This way, when we unpack it in `\g__block_labels_box` it correctly remains boxed in those cases. Afterwards, in the `newline` case add `\newline` if the label did not fit in the allotted space.

```

524     {
525     \__block_debug_typeout:n{template:item:std}

```

First deal with the key-value input, which in particular may provide a value for the label (the usual optional argument of `\item`). For this we set `\l__block_label_given_tl` to `\c_novalue_tl` so that we can identify if an optional argument was given.

```
526     \tl_set_eq:NN \l__block_label_given_tl \c_novalue_tl
```

First we evaluate and set any keys specified on the list environment by calling `__block_evaluate_saved_user_keys:nn`. Then we do the same with all keys specified on this `\item` command (which may overwrite one or the other setting just made).

```
527     \__block_evaluate_saved_user_keys:nn {item}{std}
```

We don't care whether all of the user keys from the list level have been applied, but those explicitly set on the `\item` command should be applicable, so we generate an error if that isn't the case:

```

528     \SetKnownTemplateKeys{item}{std}{#1}
529     \tl_if_empty:NF \UnusedTemplateKeys
530     {
531         \msg_error:nne{block}{unknown-keys}
532         { \noexpand\item command }
533         \UnusedTemplateKeys
534     }

```

If no optional argument was given then `\l__block_label_given_tl` is still equal to `\c_novalue_tl` and so we can distinguish that from `\item[]`.

```

535     \tl_if_novalue:oTF \l__block_label_given_tl
536     {

```

fix

The rest of the code for this template needs work and is both incomplete and partly wrong.

```
537     \tl_if_blank:oF \clistctr { \kernel@refstepcounter \clistctr }
538     \bool_if:NTF \l__block_item_compatibility_bool    % not sure that
539                                         % conditional
540                                         % makes sense
541     { \__block_make_label_box:n { \MakeLinkTarget[\clistctr]{\clistctr}%
542                                     \citemlabel } } % TODO ?
543     { \__block_make_label_box:n { \MakeLinkTarget[\clistctr]{\clistctr}%
544                                     \__block_counter_label:n { \clistctr } } }
545   }
546   {
547     \__block_debug_typeout:n{item~ with~ optional}
548     \__block_make_label_box:n { \l__block_label_given_tl } }
\bool_if:nT
{
  \l__block_label_boxed_bool
% TODO: is \ linewidth correct?
  && \dim_compare_p:n
      { \box_wd:N \l__block_one_label_box <= \ linewidth }
}
{
  \dim_compare:nNnT
  { \box_wd:N \l__block_one_label_box } < \labelwidth
  {
    \hbox_set_to_wd:Nnn \l__block_one_label_box { \labelwidth }
    {
      \exp_after:wN \use_i:nn \l__block_item_align_tl
    }
  }
}
```

FMi: L^AT_EX 2 _{ε} keeps the label boxed inside (not unboxed). This means that the content stays rigid and does not vary based on glue setting in the line with the label. There are cases where we do want the unboxed version (I think enumitem offers that in some cases too) but it should probably not be the default.

```
563 %
      TODO: customize?
564 %
      \hbox_unpack_drop:N \l__block_one_label_box
      \box_use_drop:N \l__block_one_label_box
      \exp_after:wN \use_i:nn \l__block_item_align_tl
}
}
```

Add another box level to the label box:

```
569     \hbox_set:Nn \l__block_one_label_box
570             { \box_use_drop:N \l__block_one_label_box }
571   }
572 \dim_compare:nNnTF { \box_wd:N \l__block_one_label_box } > \labelwidth
573   { \bool_set_true:N \l__block_long_label_bool }
574   { \bool_set_false:N \l__block_long_label_bool }
575 \hbox_gset:Nn \g__block_labels_box
{
  \hbox_unpack_drop:N \g__block_labels_box
  \skip_horizontal:n { \itemindent - \labelsep - \labelwidth }
  \hbox_unpack_drop:N \l__block_one_label_box
  \skip_horizontal:n { \labelsep }
  \bool_if:NT \l__block_next_line_bool
```

```

582     { \bool_if:NT \l__block_long_label_bool { \nobreak \hfil \break } }
583     % version of \newline inside an hbox that will be unpacked
584   }
585   % TODO??? FMi what's that?
586   % \skip_set_eq:NN \parsep \l__block_item_parsep_skip

```

The next setting is for compatibility: The list template sets `\listparindent` to zero and otherwise doesn't use it any more. However, in the second argument of a legacy `list` environment the user may have set it explicitly to some other value and whatever value it had was then used for `\parindent` within the list. Now we use its value only if it differs from zero but otherwise use whatever the template instances specify. This gives 99.9% compatibility for legacy documents. 100% for definitions using the `list` environment and a setting inside, but if the user used `\listparindent` within the document, e.g., inside a `verse` environment there is one case in which the setting is ignored, i.e., when it was set back to zero. That's a rather unlikely scenario, but it is not impossible. However, I couldn't think of an approach that circumvents such boundary cases.

```

587   \dim_compare:nNnF \listparindent = {0pt}
588   { \dim_set_eq:NN \parindent \listparindent }

```

Placing the list label(s) is done when the paragraph for the `\item` is started, which executes `__block_item_everypar:` inside `para/begin`. By default this command does nothing, now we change it to attach the pending label or labels.

```

589   \cs_set_eq:NN \__block_item_everypar: \__block_item_everypar_std:
590   }

```

`\l__block_item_align_tl`

```
591 \tl_new:N \l__block_item_align_tl
```

(*End of definition for `\l__block_item_align_tl`.*)

`\l__block_one_label_box`
`\g__block_labels_box`

Each label is typeset in `\l__block_one_label_box` to be measured. Once this is ready, it is put (boxed or unboxed) in `\g__block_labels_box`, together with any pending labels (for the case where a list begins just after `\item`). This is an analogue of L^AT_EX 2_<'s `\@labels`, but it is always unboxed before use, to support both boxed and unboxed labels.

```

592 \box_new:N \l__block_one_label_box
593 \box_new:N \g__block_labels_box

```

(*End of definition for `\l__block_one_label_box` and `\g__block_labels_box`.*)

`\l__block_long_label_bool` Track whether the `\l__block_one_label_box` is larger than `\labelwidth`.

```
594 \bool_new:N \l__block_long_label_bool
```

(*End of definition for `\l__block_long_label_bool`.*)

`__block_make_label_box:n`
`__block_label_format:e` Make one label, wrapped in `__block_label_format:n`, with an appropriate `\strut` and possibly `\makelabel` in compatibility mode (used for the `list` environment).

```

595 \cs_new_protected:Npn \__block_make_label_box:n #1
596   {
597     \hbox_set:Nn \l__block_one_label_box
598     {

```

If we do tagging then the contents of this box may need to be wrapped into a structure, e.g., <Lbl>.

```

599      \__kernel_list_label_begin:
600      \__block_label_format:n
601      {
602          \bool_if:NT \l__block_label_strut_bool { \strut }
603          \bool_if:NTF \l__block_legacy_support_bool
604              \makelabel
605              \use:n
606              {#1}
607      }

```

And what gets opened also needs closing:

```

608      \__kernel_list_label_end:
609      }
610  }

```

(End of definition for __block_make_label_box:n and __block_label_format:e.)

__kernel_list_label_begin:
__kernel_list_label_end:

If we aren't doing tagging the kernel hooks do nothing.

```

611 \cs_new_eq:NN \__kernel_list_label_begin: \prg_do_nothing:
612 \cs_new_eq:NN \__kernel_list_label_end: \prg_do_nothing:

```

(End of definition for __kernel_list_label_begin: and __kernel_list_label_end:.)

__block_item_everypar:
__block_item_everypar_std:
__block_item_everypar_first:

The __block_item_everypar: command is executed as part of para/begin but most of the time does nothing, i.e., it has the following default definition outside of lists (and most of the time within lists).

```

613 \cs_new_eq:NN \__block_item_everypar: \prg_do_nothing:
614 \AddToHook{para/begin}[items]{\__block_item_everypar:}

```

Note that we have to make sure that the above code is executed after the hook chunk from tagpdf because the latter uses @inlabel to make a decision.

By the end of the day both should probably move into the kernel hook instead or, better, into sockets.

```
615 \DeclareHookRule{para/begin}{items}{after}{tagpdf}
```

What follows is the version that resets various legacy booleans and puts the label box in the right place and finally resets itself to do nothing next time. __block_item_everypar: is set to this by the item template so that the next paragraph start runs the code below.

```

616 \cs_new_protected:Npn \__block_item_everypar_std: {
617     \__block_debug_typeout:n{item~ everypar \on@line }
618     \legacy_if_set_false:n { @minipage }
619     \legacy_if_gset_false:n { @newlist }
620     \legacy_if:nT { @inlabel }
621     {
622         \legacy_if_gset_false:n { @inlabel }
623         \box_if_empty:NT \g_para_indent_box { \kern - \itemindent }
624         \para omit indent:
625         \box_use_drop:N \g__block_labels_box

```

After the labels are placed we start a paragraph structure (if appropriate). This is handled in the following kernel hook:

```

626         \__kernel_list_label_after:
627             \penalty \c_zero_int
628         }
629     \legacy_if:nTF { @nobreak }
630     {
631         \legacy_if_gset_false:n { @nobreak }
632         \int_set:Nn \clubpenalty { 10000 }
633     }
634     {
635         \int_set_eq:NN \clubpenalty \@clubpenalty

```

Once the label(s) are typeset and we are past any special `@nobreak` handling we reset `__block_item_everypar:` to do nothing.

```

636         \cs_set_eq:NN \__block_item_everypar: \prg_do_nothing:
637     }
638 }

```

This is the definition of `__block_item_everypar:` before the first `\item` is encountered.

```

639 \cs_new:Npn \__block_item_everypar_first: {
640     \legacy_if:nT { @newlist } { \noitemerr }
641 }

```

(End of definition for `__block_item_everypar:`, `__block_item_everypar_std:`, and `__block_item_everypar_first::`)

```
\__kernel_list_label_after:
642 \cs_new_eq:NN \__kernel_list_label_after: \prg_do_nothing:
(End of definition for \__kernel_list_label_after::)
```

```
\l__block_tmpa_skip
643 \skip_new:N \l__block_tmpa_skip
(End of definition for \l__block_tmpa_skip.)
```

`\l__block_topsepadd_skip` `\l__block_effective_top_skip` Variables equivalent to L^AT_EX 2_C's `\@topsepadd` and `\@topsep`. Roughly equal to a mixture of `topsep`, `partopsep`, and various `parskip` at different nesting levels in lists. The code is really elaborate when `@inlabel` is true.

```

644 \skip_new:N \l__block_topsepadd_skip
645 \skip_new:N \l__block_effective_top_skip

```

(End of definition for `\l__block_topsepadd_skip` and `\l__block_effective_top_skip`.)

item Here we already have all the building blocks. Complain in math mode. Distinguish between first item (do necessary tagging) and later items `__block_inter-item:` to cleanly close what's before, then call `__block_item_instance:n` (which calls `\UseInstance{item}{\langle instance \rangle}`) to prepare the upcoming item: it will be actually inserted only once some later material triggers `\everypar`.

```

646 \AddToHook{begindocument/before}{
647     \RenewDocumentCommand{\item}{ ={label}o }
648     {
649         \@inmatherr \item

```

TODO: Check if test for being outside of a list is sensible

```

650      \cs_if_free:NNTF \__block_item_instance:n
651      {
652          \@latex@error{Lonely~\string\item--perhaps-a-missing-
653                      list-environment}\@ehc
654      }
655      {
656          \legacy_if:nTF { @newlist }
657          {
658              \__kernel_list_item_begin:

```

The first item of a list also has to change the `@newlist` switch.

```

659          \legacy_if_gset_false:n { @newlist }
660      }
661      { \__block_inter_item: }

```

To avoid unnecessary key/val processing we make a quick check if there was an optional argument.

```

662          \tl_if_no_value:nTF {#1}           % avoids reparsing label={}
663          { \__block_item_instance:n { } }
664          { \__block_item_instance:n {#1} }

```

Set the legacy switch that signals that we have a pending item label:

```

665          \legacy_if_gset_true:n { @inlabel }
666          \ignorespaces
667      }
668  }
669 }

```

(End of definition for `\item`. This function is documented on page 12.)

`__block_inter_item:` Between items. If the previous item had no content then we need to trigger `\everypar`. Otherwise we simply close the previous item with `\par` after removing some horizontal space. Between items, there is a penalty and some space.

```

670 \cs_new_protected:Npn \__block_inter_item: {
671     \legacy_if:nT { @inlabel }
672         { \indent \par } % case of \item\item

```

`\par` may have a strange definition and may not get us back to vertical mode in one go, so we better do not treat the next line as an else case to the above conditional (for now).

```

673     \mode_if_horizontal:T { \__block_skip_remove_last:
674                             \__block_skip_remove_last: \par }

```

End any LI-tag, then start the next LI-tag (if doing tagging):

```

675     \__kernel_list_item_end:
676     \__kernel_list_item_begin:
677     \addpenalty \itempenalty
678     \addvspace \itemsep
679 }

```

(End of definition for `__block_inter_item:..`)

```

\__kernel_list_item_begin:
\__kernel_list_item_end:
680 \cs_new_eq:NN \__kernel_list_item_begin: \prg_do_nothing:
681 \cs_new_eq:NN \__kernel_list_item_end: \prg_do_nothing:

```

(End of definition for `__kernel_list_item_begin:` and `__kernel_list_item_end:..`)

6.5 Tagging support commands

In this section we provide code to the various kernel hooks to support the tagging of different displayblock environments.

All of the following definitions should only be made if tagging is active!

```
682 \tag_if_active:TF {
```

- __block_beginpar_vmode: When a block starts out in vertical mode, i.e., is not yet part of a paragraph, we have to start a paragraph structure. However, this is not the case if we are already flattening paragraphs, thus in this case we do nothing. We also do nothing if @endpe is currently true, because that means we are right now just after the end of a `blockenv` and in the process of looking if we have to end the current `<text-unit>`, i.e., it is already open.

```
683 \cs_set:Npn \__block_beginpar_vmode: {
684     \__block_debug_typeout:n
685         { @endpe = \legacy_if:nTF { @endpe }{true}{false}
686             \on@line }
687     \legacy_if:nTF { @endpe }
688     {
689         \legacy_if_gset_false:n { @endpe }
690     }
```

We test for <2 because the first flattened environment has to surround itself with a `<text-unit>`. Only any inner ones then have to avoid adding another `<text-unit>`.

```
691 {
692     \int_compare:nNnT \l__tag_block_flattened_level_int < 2
693     {
694         \__tag_gincr_para_main_begin_int:
695         \tag_struct_begin:n
696         {
697             tag=\l__tag_para_main_tag_tl,
698             attribute-class=\l__tag_para_main_attr_class_tl,
699         }
700         \__tag_para_main_store_struct:
701     }
702 }
```

(End of definition for __block_beginpar_vmode:.)

- __block_beginpar_hmode:N If the block is already part of a part of a paragraph, i.e., when it has some text directly in front, then the first thing to do is to return to vertical mode. However, that should be done without inserting a paragraph end tag, so before calling `\par` to do its normal work, we disable paragraph tagging and restarting afterwards again. The argument to this config point simply gobbles the `\par` following it in the code above (which is used when there is no tagging going on).

```
704 \cs_set:Npn \__block_beginpar_hmode:N #1
705 {
706     \tag_mc_end:
707     \__tag_gincr_para_end_int:
708     \__block_debug_typeout:n{increment~ /P \on@line }
709     \bool_if:NT \l__tag_para_show_bool
710     { \tag_mc_begin:n{artifact}
711         \rlap{\color_select:n{red}\tiny\ \int_use:N\g__tag_para_end_int}
```

```

712           \tag_mc_end:
713       }
714   \tag_struct_end:
715   \tagpdfparaOff \par \tagpdfparaOn
716 }

```

(End of definition for `_block_beginpar_hmode:N.`)

`_kernel_displayblock_doendpe:` If a display block ends and is followed by a blank line we have to end the enclosing paragraph tagging structure.

```

717 \cs_set:Npn \_kernel_displayblock_doendpe: {
718     \bool_if:NT \l__tag_para_bool
719     {

```

Given that restoring `\par` through the legacy L^AT_EX 2_E method can take a few iterations (for example, in case of nested lists, e.g., $\dots \end{itemize} \item \dots \par$ it can happen that `_kernel_displayblock_doendpe:` is called while `\endpe` is already handled and then we should not attempt to close a `<text-unit>` structure). So we need to check for this.

```

720     \legacy_if:nT { \endpe }
721     {

```

If the display block currently ending was “flattened” (i.e., uses simplified paragraphs that are not tagged by a combination of `<text-unit>` followed by `<text>`, but simply with a `<text>`), then we don’t have to do anything, because the `<text>` is already closed.

```

722     \_block_debug_typeout:n
723     { flattened= \bool_if:NTF
724         \l__tag_para_flattened_bool
725         {true}{false}
726         \on@line }
727     \bool_if:NF \l__tag_para_flattened_bool
728     {
729         \_block_debug_typeout:n{Structure-end-
730         \l__tag_para_main_tag_tl\space
731         after~ displayblock \on@line      }
732         \_tag_gincr_para_main_end_int:
733         \tag_struct_end: %text-unit
734     }
735 }
736 }
737 }

```

(End of definition for `_kernel_displayblock_doendpe:.`)

para/begin Paragraph tagging is mainly done using the paragraph hooks (will get moved eventually). The default hook setting is not good enough when lists get supported: we need to delay starting the paragraph tagging if we still have to place the list label. We therefore remove the existing hook data and replace it with an augmented version (this will get combined eventually).

```

738 \RemoveFromHook{para/begin}[tagpdf]
739 \AddToHook{para/begin}[tagpdf]{
740     \bool_if:NT \l__tag_para_bool {

```

if we are still waiting to typeset the list label we do nothing (the paragraph tagging then happens when the list is finally typeset).

```
741     \legacy_if:nF { @inlabel }
742     {

```

Otherwise, we start a `<text>` tag structure but only if we are not starting a paragraph immediately *after* a list, in which case we only start a new MC (because the `<text>` tag is still open from before the list — one of the reasons why lists are always put “inside” paragraphs).

We do this in a separate command, because it is needed elsewhere too.

```
743     \__block_start_para_structure:n { \PARALABEL }
744     }
745   }
746 }
```

```
\__block_start_para_structure:n
747 \cs_new_protected:Npn \__block_start_para_structure:n #1 {
748   \__block_debug_typeout:n
749   { @endpe = \legacy_if:nTF { @endpe }{true}{false}
750     \on@line
751   \legacy_if:nF { @endpe }
752   {
753     \bool_if:NF \l__tag_para_flattened_bool
754     {
755       \__tag_gincr_para_main_begin_int:
756       \tag_struct_begin:n
757       {
758         tag=\l__tag_para_main_tag_tl,
759         attribute-class=\l__tag_para_main_attr_class_tl,
760       }
761       \__tag_para_main_store_struct:
762     }
763   }
764   \__tag_gincr_para_begin_int:
765   \__block_debug_typeout:n{increment~ P \on@line }
766   \tag_struct_begin:n
767   {
768     tag=\l__tag_para_tag_tl
769     ,attribute-class=\l__tag_para_attr_class_tl
770   }
771   \__tag_check_para_begin_show:nn {green}{#1}
772   \tag_mc_begin:n {}
773 }
```

The same code, but without testing `@endpe`. This is not needed in the standalone case and wrong inside lists.

```
774 \cs_new_protected:Npn \__block_start_para_structure_unconditionally:n #1 {
775   \bool_if:NF \l__tag_para_flattened_bool
776   {
777     \__tag_gincr_para_main_begin_int:
778     \tag_struct_begin:n
779     {
780       tag=\l__tag_para_main_tag_tl,
781       attribute-class=\l__tag_para_main_attr_class_tl,
```

```

782         }
783         \__tag_para_main_store_struct:
784     }
785 \__tag_gincr_para_begin_int:
786 \__block_debug_typeout:n{increment~ P \on@line }
787 \tag_struct_begin:n
788 {
789     tag=\l__tag_para_tag_tl
790     ,attribute-class=\l__tag_para_attr_class_tl
791 }
792 \__tag_check_para_begin_show:nn {green}{#1}
793 \tag_mc_begin:n {}
794 }

795 \RemoveFromHook{para/end}[tagpdf]
796 \AddToHook{para/end}
797 {
798     \bool_if:NT \l__tag_para_bool
799     {
800         \__tag_gincr_para_end_int:
801         \__block_debug_typeout:n{increment~ /P \on@line }
802         \tag_mc_end:
803         \__tag_check_para_end_show:nn {red}{}
804         \tag_struct_end:
805         \bool_if:NF \l__tag_para_flattened_bool
806         {
807             \__tag_gincr_para_main_end_int:
808             \tag_struct_end:
809         }
810     }
811 }
812 \def\PARALABEL{NP-}

```

(End of definition for `para/begin` and `__block_start_para_structure:n`. This function is documented on page [12](#).)

\para_end: If we see a `\par` in vmode and a `<text-unit>` is still open we need to close that. For this we check if a request for `@endpe` was made (but the `\par` redefinition got lost due to (bad?) coding).

```

813 \cs_set_protected:Npn \para_end: {
814     \scan_stop:
815     \mode_if_horizontal:TF {
816         \mode_if_inner:F {
817             \tex_undef:D
818             \hook_use:n{para/end}
819             \kernel@after@para@end
820             \mode_if_horizontal:TF {
821                 \if_int_compare:w 11 = \tex_lastnodetype:D
822                     \tex_hskip:D \c_zero_dim
823                 \fi:
824                 \tex_par:D
825                 \hook_use:n{para/after}
826                 \kernel@after@para@after
827             }

```

```

828         { \msg_error:nnn { hooks }{ para-mode }{end}{horizontal} }
829     }
830   }
831   {
832     \__kernel_endpe_vmode:          % should do nothing if no tagging
833     \tex_par:D
834   }
835 }
836 \cs_set_eq:NN \par      \para_end:
837 \cs_set_eq:NN \__blockpar  \para_end:
838 \cs_set_eq:NN \endgraf \para_end:

```

(End of definition for `\para_end:`. This function is documented on page 12.)

\begin We need to do a little more than canceling `@endpe` now.

```

839 \DeclareRobustCommand*\begin[1]{%
840   \UseHook{env/#1/before}%
841   \Ifundefined{#1}%
842     {\def\reserved@a{\@latex@error{Environment~#1~undefined}\@eha}%
843     \def\reserved@a{\def\currenvir{#1}%
844       \edef\currenvline{\on@line}%
845       \@execute@begin@hook{#1}%
846       \csname #1\endcsname}%
847   \ignorespaces
848   \begingroup
849     \__kernel_endpe_vmode:
850     \reserved@a}

```

(End of definition for `\begin`. This function is documented on page 12.)

`__kernel_endpe_vmode:` Close an open `<text-unit>` if `@endpe` is true and we are in vmode. Used in `\para_end:` and `\begin`.

```

851 \cs_new:Npn \__kernel_endpe_vmode: {
852   \if@endpe \ifvmode
853     \bool_if:NT \l__tag_para_bool
854   {
855     \bool_if:NF \l__tag_para_flattened_bool
856     {
857       \__tag_gincr_para_main_end_int:
858       \tag_struct_end:
859     }
860     \endpefalse
861   }
862   \fi \fi
863 }

```

(End of definition for `__kernel_endpe_vmode:.`)

`__kernel_list_label_after:` If starting the text-unit/text tags got delayed because of a pending label we have to do it after the label got typeset

```

864 \cs_set:Npn \__kernel_list_label_after: {
865   \bool_if:NT \l__tag_para_bool
866   {
867     \__block_start_para_structure_unconditionally:n { LI- }
868   }
869 }

```

(End of definition for `_kernel_list_label_after:.`)

`_block_inner_begin:` Start a block that has an inner structure if it isn't also a list.

```
870 \cs_new:Npn \_block_inner_begin: {
871     \tagstructbegin{tag=\l__block_tag_inner_tag_tl}
872 }
```

(End of definition for `_block_inner_begin:.`)

`_block_inner_end:` End a block (which isn't also a list).

```
873 \cs_new:Npn \_block_inner_end: {
874     \_block_debug_typeout:n{block-end \on@line}
875     \legacy_if:nT { @endpe }
876     {
877         \_tag_gincr_para_main_end_int:
878         \_block_debug_typeout:n{close~ /text-unit \on@line}
879         \tagstructend
880     }
881     \tagstructend      % end inner structure
882 }
```

(End of definition for `_block_inner_end:.`)

6.5.1 List tags

```
883 \tl_new:N \l__tag_L_tag_tl
884 \tl_set:Nn \l__tag_L_tag_tl {L}
885
886 \tl_new:N\l__tag_L_attr_class_tl
887 \tl_set:Nn \l__tag_L_attr_class_tl {list}
888 \tag_if_active:T
889 {
890     \tagpdfsetup
891     {
892         role/new-attribute = {itemize}
893             {/0 /List /ListNumbering/Unordered},
894         role/new-attribute = {enumerate}
895             {/0 /List /ListNumbering/Ordered},
896         role/new-attribute = {description}
897             {/0 /List /ListNumbering/Description},
```

Initially, we had `/None` for the basic `list` environment, but that is not allowed in PDF/UA-2 if the list contains any Lbl tags. So now we default to `Unordered`.

```
898     % default if unknown
899     role/new-attribute = {list}{/0 /List /ListNumbering/Unordered},
900 }
901 }
902 \def\LItag{LI}
```

`_block_list_begin:` Start a list ...

```
903 \cs_set:Npn \_block_list_begin: {
904     \tagstructbegin
905     {
906         tag=\l__tag_L_tag_tl
```

```

907         ,attribute-class=\l__tag_L_attr_class_t1
908     }
909 }
```

(End of definition for __block_list_begin:.)

__block_list_item_begin: Start tagging a list item.

```

910 \cs_set:Npn \_\_block_list_item_begin: { \tagstructbegin{tag=\LITag} }
911 %
```

(End of definition for __block_list_item_begin:.)

__kernel_list_label_begin: A list label needs a <Lbl> structure tag and an MC.

```

911 \cs_set:Npn \_\_kernel_list_label_begin: {
912 %
913 % FMI: this needs a different logic to decide when to make the label
914 %      an artifact (after cleaning up the \item code ), therefore
915 %      disabled for now
916 % \tl_if_empty:oTF \@itemlabel
917 %
918 %      \tag_mc_begin:n {artifact}
919 %
920 %
921     \tagstructbegin{tag=Lbl}
922     \tagmcbegin{tag=Lbl}
923 %
924 }
```

(End of definition for __kernel_list_label_begin:.)

__kernel_list_label_end: And when we are done with the label we have to close the MC and the <Lbl> structure. We then start the <LBody>. The material inside will be “paragraph” text and the tagging for that is handled by the normal para tagging.

```

925 \cs_set:Npn \_\_kernel_list_label_end: {
926     \tagmcend                                     % end mc-Lbl or artifact
927 %
928 % FMI: unconditionally for now
929 % \tl_if_empty:oF \@itemlabel
930     \tagstructend % end Lbl
931     \tagstructbegin{tag=\LBody}
932 }
```

(End of definition for __kernel_list_label_end:.)

__block_list_item_end: When a list item ends we have to close <LBody> and but also a <text> in the special case that the item material ends in a list (identifiable via @endpe).

```

933 \cs_set:Npn \_\_block_list_item_end: {
934     \legacy_if:nT { @endpe }
935     {
936         \_\_tag_gincr_para_main_end_int:
937         \tagstructend                               % text-unit
938 %         \_\_block_debug_typeout:n{Structure-end~ P~ at~ item-end \on@line }
939     }
940     \tagstructend \tagstructend    % end LBody, LI
941 }
```

(End of definition for `_block_list_item_end`.)

`_block_list_end`: Finally, at the list end we have to close the open `<LBody>`, ``, `<L>`, and possibly a `<text>` if the last item ends with a list. However, if the user forgot to add an `\item` then there will be no `` and `<LBody>` open, so we check for the status of `@newlist`. The corresponding no-item error was generated earlier outside the tagging code.

One could argue that it doesn't matter if the tagging is wrong after a `\@noitemerr` was issued. However, there is one case where it isn't an error: In the `thebibliography` environment (which is internally a list) it is often the case that documents start out with an empty environment, not containing any `\bibitems`. For that reason `\@noitemerr` is redefined inside that environment to only produce a warning; hence we have to produce correct tag structures in that case.

```
942 \cs_set:Npn \_block_list_end: {
```

If `@newlist` is true (i.e., when we have an error or warning situation) there is not much to close.

```
943     \legacy_if:nF { @newlist }
944     {
945         \legacy_if:nT { @endpe }
946         {
947             \_tag_gincr_para_main_end_int:
948             \tagstructend % text-unit
949             \_block_debug_typeout:n{Structure-end~ P~ at~ list-end \on@line }
950         }
951         \tagstructend\tagstructend % end LBody, LI
952     }
953     \tagstructend % end L
954 }
```

(End of definition for `_block_list_end`.)

End of tagging related declarations.

```
955 }
```

These command should have a dummy declaration if tagging is not active

```
956 {
957     \cs_new:Npn \_block_start_para_structure_unconditionally:n #1 {}
958 }
```

6.6 Tagging recipes

`_block_recipe_basic`: The `basic` recipe simply ensures that the block is inside a `<text-unit>` structure and if necessary starts one. When the block ends and is followed by a blank line the `<text-unit>` structure is closed too, otherwise it remains open and further text starts with just a `<text>` structure.

There is otherwise no inner structure so `_kernel_displayblock_begin:` and `_kernel_displayblock_end:` do nothing—blockenvs with inner structure use the `standard` or `list` recipe instead.

```
959 \cs_new:Npn \_block_recipe_basic: {
960     \cs_set_eq:NN \_kernel_displayblock_beginpar_hmode:w
961                                         \_block_beginpar_hmode:N
962     \cs_set_eq:NN \_kernel_displayblock_beginpar_vmode:
963                                         \_block_beginpar_vmode:
964     \let \_kernel_displayblock_begin:           \prg_do_nothing:
965     \let \_kernel_displayblock_end:            \prg_do_nothing:
```

End environment \par handling:

```
966   \socket_assign_plug:nn{tagsupport/block-endpe}{on}
967 }
```

(End of definition for __block_recipe_basic:.)

__block_recipe_standalone: The **standalone** recipe produces a block that ensures that a previous <text-unit> ends and that after the block a new <text-unit> starts.

```
968 \cs_new:Npn \_\_block_recipe_standalone: {
969   \cs_set_eq:NN \_\_kernel_displayblock_beginpar_hmode:w
970   \prg_do_nothing:
971   \cs_set_eq:NN \_\_kernel_displayblock_beginpar_vmode:
972   \prg_do_nothing:
973   \cs_set_eq:NN \_\_kernel_displayblock_begin: \_\_block_inner_begin:
974   \cs_set_eq:NN \_\_kernel_displayblock_end: \_\_block_inner_end:
```

End environment \par handling:

```
975   \socket_assign_plug:nn{tagsupport/block-endpe}{off}
976   \tl_if_empty:NTF \l__block_tag_name_tl
977     { \tl_set:Nn \l__block_tag_inner_tag_tl {Sect} }
978     { \tl_set_eq:NN \l__block_tag_inner_tag_tl \l__block_tag_name_tl }
979 }
```

(End of definition for __block_recipe_standalone:.)

__block_recipe_standard: The **standard** recipe does the following:

- surround the block with a <text-unit> structure if not already in a a <text-unit>. In the latter case end the MC and the <text> but leave the <text-unit> open.
If we are producing flattened paragraphs, just close any <text> but do not open a <text-unit>.
- Then open an new (inner) structure (by default <Figure> but typically the one specified on the instance).
- At the end of the block close the inner structure (<Figure> or explicit one) but leave the <text-unit> open to be either continued or closed due to a following \par.

```
980 \cs_new:Npn \_\_block_recipe_standard:
981 {
982   \cs_set_eq:NN \_\_kernel_displayblock_beginpar_hmode:w
983   \_\_block_beginpar_hmode:N
984   \cs_set_eq:NN \_\_kernel_displayblock_beginpar_vmode:
985   \_\_block_beginpar_vmode:
986   \cs_set_eq:NN \_\_kernel_displayblock_begin: \_\_block_inner_begin:
987   \cs_set_eq:NN \_\_kernel_displayblock_end: \_\_block_inner_end:
```

End environment \par handling:

```
988   \socket_assign_plug:nn{tagsupport/block-endpe}{on}
989   \tl_if_empty:NTF \l__block_tag_name_tl
990     { \tl_set:Nn \l__block_tag_inner_tag_tl {Figure} }
991     { \tl_set_eq:NN \l__block_tag_inner_tag_tl \l__block_tag_name_tl }
992 }
```

(End of definition for `_block_recipe_standard`.)

```
\l__block_tag_inner_tag_tl
 993 \tl_new:N \l__block_tag_inner_tag_tl
(End of definition for \l__block_tag_inner_tag_tl.)
```

`_block_recipe_list`: The list recipe does the following.

- It opens a `<text-unit>`-structure or keeps the current one open (only closing the MC).
- It then starts a new structure rolemapped to L-structure and arranges for handling list items, e.g., Li, Lbl and LBody structures.
- At the end it closes open list structures as needed but keeps the `<text-unit>`-structure open to continue the paragraph after the list, if necessary.

```
994 \cs_new:Npn \_block_recipe_list:
995 {
 996   \cs_set_eq:NN \__kernel_displayblock_beginpar_hmode:w
 997   \__block_beginpar_hmode:N
 998   \cs_set_eq:NN \__kernel_displayblock_beginpar_vmode:
 999   \__block_beginpar_vmode:
1000   \cs_set_eq:NN \__kernel_displayblock_begin: \__block_list_begin:
1001   \cs_set_eq:NN \__kernel_displayblock_end: \__block_list_end:
```

The next two lines could be done globally, because they are only called if we do have `\items`, i.e., if we are in a list. It is therefore also not necessary to reset them in other recipes (right now—this may change if we get more templates (like inline lists)).

```
1002 \cs_set_eq:NN \__kernel_list_item_begin: \__block_list_item_begin:
1003 \cs_set_eq:NN \__kernel_list_item_end: \__block_list_item_end:
```

End environment `\par` handling:

```
1004 \socket_assign_plugin:nn{tagsupport/block-endpe}{on}
```

Handle the tag name and attribute classes using the key values from the current list instance.

```
1005 \tl_if_empty:NTF \l__block_tag_name_tl
1006   { \tl_set:Nn \l__tag_L_tag_tl {L} }
1007   { \tl_set_eq:NN \l__tag_L_tag_tl \l__block_tag_name_tl }
1008 \tl_if_empty:NTF \l__block_tag_class_tl
1009   { \tl_set:Nn \l__tag_L_attr_class_tl {} }
1010   { \tl_set_eq:NN \l__tag_L_attr_class_tl \l__block_tag_class_tl }
1011 }
```

(End of definition for `_block_recipe_list`.)

7 Implementation of document-level block environments

Most such environments are pretty simple: they take an optional argument and call a `blockenv` instance to do the work. At the end of environment we call `\endblockenv` to finish.

7.1 Displayblock environments

There are two basic block environment which are similar to L^AT_EX 2_&'s `trivlist` except that there aren't degenerated lists and thus have no hidden `\item` inside.

```
displayblock (env.)  
1012 \NewDocumentEnvironment{displayblock}{ !O{} }  
1013 { \UseInstance{blockenv}{displayblock} {#1} }  
1014 { \endblockenv }  
  
displayblockflattened (env.)  
1015 \NewDocumentEnvironment{displayblockflattened}{ !O{} }  
1016 { \UseInstance{blockenv}{displayblockflattened} {#1} }  
1017 { \endblockenv }
```

7.2 The `center`, `flushleft`, and `flushright` environments

```
center (env.)  
flushleft (env.) 1018 \AddToHook{begindocument/before}{  
flushright (env.) 1019 \RenewDocumentEnvironment{center}{ !O{} }  
1020 { \UseInstance{blockenv}{center}{#1} }  
1021 { \endblockenv }  
1022 \RenewDocumentEnvironment{flushright}{ !O{} }  
1023 { \UseInstance{blockenv}{flushright}{#1} }  
1024 { \endblockenv }  
1025 \RenewDocumentEnvironment{flushleft}{ !O{} }  
1026 { \UseInstance{blockenv}{flushleft}{#1} }  
1027 { \endblockenv }  
1028 }
```

7.3 Display quote environments

```
quote (env.)  
quotation (env.) 1029 \AddToHook{begindocument/before}{  
1030 \RenewDocumentEnvironment{quote}{ !O{} }  
1031 { \UseInstance{blockenv}{quote}{#1} }  
1032 { \endblockenv }  
1033 \RenewDocumentEnvironment{quotation}{ !O{} }  
1034 { \UseInstance{blockenv}{quotation}{#1} }  
1035 { \endblockenv }  
1036 }
```

7.4 Verbatim environments

```
verbatim (env.)  
verbatim* (env.) 1037 \AddToHook{begindocument/before}{  
1038 \RenewDocumentEnvironment{verbatim}{ !O{} }  
1039 { \UseInstance{blockenv}{verbatim}{#1}}
```

This is the part of the code where `verbatim` and `verbatim*` differ.

```

1040      \c@setupverbinspace\frenchspacing\c@vobeyspaces
1041      \c@xverbatim
1042    }
1043    { \endblockenv }

1044 \RenewDocumentEnvironment{verbatim*}{!O{}}
1045   { \UseInstance{blockenv}{verbatim} {#1}
1046     \c@setupverbinspace\frenchspacing\c@vobeyspaces
1047     \c@sxverbatim
1048   }
1049   { \endblockenv }
1050 }
```

7.4.1 Helper commands for verbatim

`\legacyverbatimsetup`

This code resembles the L^AT_EX 2 _{ε} `verbatim` implementation with a slight twist: in L^AT_EX 2 _{ε} each code line was a paragraph using `\leftskip=\@totalleftmargin`. This was possible because the whole environment was implemented as a trivlist. As this is no longer the case setting `\leftskip` would alter the layout of a surrounding list. So instead we need to make sure that the paragraph end is executed in a group so that any parshape setup is preserved.

```

1051 <@@=›
1052 \def\legacyverbatimsetup{%
1053   \language\l@nohyphenation
1054   \c@tempswafalse
1055   \def\par{%
1056     \if@ctempswa
1057       \leavevmode \null {\@par}\penalty\interlinepenalty
1058     \else
1059       \c@tempswatrue
1060       \ifhmode{\@par}\penalty\interlinepenalty\fi
1061     \fi}%
1062   \let\do\@makeother \dospecials
1063   \obeylines \verbatim@font \noligs
1064   \everypar \expandafter{\the\everypar \unpenalty}%
1065   \tl_set:Nn \l__tag_para_tag_tl {codeline}
1066 }
1067 <@@=block>
```

(End of definition for `\legacyverbatimsetup`. This function is documented on page 11.)

`\c@setupverbinspace`

In the pdfL^AT_EX engine we need to use `\pdffakespace` chars for the invisible spaces.

```

1068 \newcommand\c@setupverbinspace{}
1069 \tag_if_active:T {
1070   \bool_if:NF\g__tag_mode_lua_bool
1071   {
1072     \renewcommand\c@setupverbinspace
1073       {\def\c@xobeysp{\nobreakspace\pdffakespace}}
1074   }
1075 }
```

(End of definition for `\c@setupverbinspace`. This function is documented on page 11.)

7.5 Standard list environments

```
itemize (env.) For the standard lists everything is managed by the blockenv instance.  
enumerate (env.) 1076 \AddToHook{begindocument/before}{  
description (env.) 1077 \RenewDocumentEnvironment{itemize}{!0{}{}}  
1078 { \UseInstance{blockenv}{itemize} {#1} }  
1079 { \endblockenv }  
1080 \RenewDocumentEnvironment{enumerate}{!0{}{}}  
1081 { \UseInstance{blockenv}{enumerate} {#1} }  
1082 { \endblockenv }  
1083 \RenewDocumentEnvironment{description}{!0{}{}}  
1084 { \UseInstance{blockenv}{description} {#1} }  
1085 { \endblockenv }  
1086 }
```

7.6 verse environment

verse (env.) The verse environment has not special tagging currently. It is defined as a simple standard list and takes the tagging from there. But it must be redefined so that \itemindent is correctly set.

```
1087 \AddToHook{begindocument/before}{  
1088 \RenewDocumentEnvironment{verse}{ !0{} }  
1089 {  
1090     \let\\@centercr  
1091     \UseInstance{blockenv}{list}  
1092     {  
1093         item-indent=-1.5em,  
1094         parindent=-1.5em,  
1095         item-skip=0pt,  
1096         rightmargin=\leftmargin,  
1097         leftmargin=\leftmargin+1.5em,  
1098         #1  
1099     }  
1100     \item\relax  
1101 }  
1102 { \endblockenv }  
1103 }
```

list (env.) The legacy 2e list environment is more complicated as we have to get the extra arguments accounted for.

```
1104 \AddToHook{begindocument/before}{  
1105 \RenewDocumentEnvironment{list}{0{} m m }  
1106 {
```

We do this by storing them away and then call the list instance. Inside this instance the `setup-code` key contains `\legacylistsetupcode`, which makes use of the stored values.

```
1107     \tl_set:Nn \l__block_legacy_env_params_tl  
1108     {  
1109         \tl_set:Nn \citemlabel {#2}  
1110         #3  
1111     }
```

```

1112     \UseInstance{blockenv}{list} {#1}
1113 }
1114 { \endblockenv
1115 }
```

\legacylistsetupcode And here is the extra code for use in the list instance setup inside the key `setup-code`.

```
1116 \cs_new:Npn \legacylistsetupcode {
```

Reset values to defaults:

```

1117     \dim_zero:N \listparindent
1118     \dim_zero:N \rightmargin
1119     \dim_zero:N \itemindent
```

By default a `list` environment is not numbered, but this happens already in the block template.

```

1120 %   \tl_set:Nn \clistctr {}
1121 %   \legacy_if_set_false:n { @nmbrlist } % needed if lists are nested
```

By default there is a simple definition for `\makelabel`. It can be overwritten in the second mandatory argument to the list environment (stored in `\l__block_legacy_env_params_tl`) and is used if the instance sets the compatibility key to true.

```
1122 \let\makelabel\@mklabel % TODO: customize
```

Now we use the argument with parameter settings to update some or all of the above defaults:

```
1123 \l__block_legacy_env_params_tl
```

As we don't know much about this list we can only make a guess about the nature of the list and the setting of the tag name (default `list` rolemapped to `<L>`) and any tag attributes may have to be overwritten in the optional key/value argument. But we do have some hints to play with.

```

1124 \legacy_if:nTF { @nmbrlist }
1125   { \tl_set:Nn \l__tag_L_attr_class_tl {enumerate} } % numbered list
1126   { \tl_if_empty:NTF \itemlabel
1127     { \tl_set:Nn \l__tag_L_attr_class_tl {list} } % no label
1128     { \tl_set:Nn \l__tag_L_attr_class_tl {itemize} } % unnumbered,
1129                                         %           % unordered
1130   }
1131 }
```

(End of definition for `\legacylistsetupcode`. This function is documented on page 11.)

```
\l__block_legacy_env_params_tl
```

```
1132 \tl_new:N \l__block_legacy_env_params_tl
```

(End of definition for `\l__block_legacy_env_params_tl`.)

Replace with code not using `\list`

```

1133 \AddToHook{begindocument/before}{%
1134   \RenewDocumentEnvironment{trivlist}{!O{}}
1135     { \list[#1]{}%
1136       {%
1137         \dim_zero:N \leftmargin
1138         \dim_zero:N \labelwidth
1139         \cs_set_eq:NN \makelabel \use:n
1140       }%
1141     }%
```

```

1141           }
1142     { \endblockenv }
1143 }

```

7.7 Theorem-like environments

Theorem-like environments are defined in L^AT_EX with the help of `\newtheorem` declarations. Internally they used a list with a single item. Using lists was convenient back then, but in a tagged document you end up with a strange structure. We therefore alter the mechanism.

`\newtheorem`

This is a slightly streamlined version of `\newtheorem`, but it still uses a lot of the 2e code for now. Eventually this will change.

```

1144 \RenewDocumentCommand \newtheorem { m O{#1} m o }
1145 {
1146   \expandafter\@ifdefinable\csname #1\endcsname
1147   {
1148     \str_if_eq:nnTF{#1}{#2}
1149     {
1150       \@definecounter{#2}
1151       \IfNoValueTF{#4}
1152       {
1153         % @ynthm
1154         \tl_gset:ce { the #2 }
1155         {
1156           \@thmcounter{#2}
1157         }
1158       }
1159       % @xnthm
1160       \@newctr{#1}[#4]
1161       \tl_gset:ce { the #2 }
1162       {
1163         \expandafter\noexpand\csname the#4\endcsname
1164         \@thmcountersep
1165         \@thmcounter{#2}
1166       }
1167     }
1168   }
1169   % @othm
1170   \@ifundefined{c@#2}
1171   {
1172     \tl_gset:cn { the #1 }
1173     { \UserName { the #2 } }
1174   }
1175 }
1176 \global\@namedef{#1} { \@thm{#2}{#3} }
1177 \global\@namedef{end#1}{ \endtheorem }
1178 }
1179 }

```

(End of definition for `\newtheorem`. This function is documented on page 11.)

`\@thm`

`\@thm` executes `\refstepcounter` too early for hyperref and structure destinations: the generated target is outside the structure and can be separated from the theorem by a page

break. We therefore move the anchor setting into `\@begintheorem`. `\@begintheorem` doesn't currently get the name of the counter as argument, so we store it in variable for now, to be able to pass it along.

```

1180 \tl_new:N \l__block_thm_current_counter_tl
1181 \def\@thm#1#2{%
1182   \qquad\@kernel@refstepcounter{#1}
1183   \tl_set:Nn \l__block_thm_current_counter_tl{#1}
1184   \qquad\@ifnextchar[{\@ythm{#1}{#2}}{\@xthm{#1}{#2}}}
```

To avoid that hyperref overwrites the definition again we must its patch:

```
1185 \def\hyper@nopatch@thm{}
```

(End of definition for `\@thm`. This function is documented on page 11.)

`\@begintheorem`
`\@opargbegintheorem`

The `\@thm` command expands to either `\@begintheorem` or `\@opargbegintheorem`. For the moment we stick with this as it will help with the transition. But instead of using a `trivlist` we use a `blockenv` and some tagging for the title (as a Caption). We do not want potential tagging from `\textbf` here, so we use `\bfseries` to set the font. The commands set also the link targets which should be inside the main structure.

```

1186 \def\@begintheorem#1#2{%
1187   \UseInstance{blockenv}{theorem}{}%
1188   \tagpdfparaOff

1189   \noindent
1190   \MakeLinkTarget{\l__block_thm_current_counter_tl}
1191   \tag_struct_begin:n{tag=Caption}
1192   \group_begin:
1193   \bfseries
1194   \tag_mc_begin:n {}
1195   #1%
1196   \tag_mc_end:
1197   \tag_struct_begin:n{tag=Lbl}
1198   \tag_mc_begin:n {}
1199   #2%
1200   \tag_mc_end:
1201   \tag_struct_end:
1202   \group_end:
1203   \tag_struct_end:
1204   \tagpdfparaOn

1205   \__block_start_para_structure_unconditionally:n { \PARALABEL }

1206   \itshape
1207   \hskip\labelsep
1208   \ignorespaces
1209 }

1210 \def\@opargbegintheorem#1#2#3{%
1211   \UseInstance{blockenv}{theorem}{}%
1212   \tagpdfparaOff

1213   \noindent
1214   \MakeLinkTarget{\l__block_thm_current_counter_tl}
1215   \tag_struct_begin:n{tag=Caption}
1216   \group_begin:
1217   \bfseries
```

```

1218     \tag_mc_begin:n {}
1219         #1\
1220     \tag_mc_end:
1221     \tag_struct_begin:n{tag=Lbl}
1222         \tag_mc_begin:n {}
1223             #2
1224         \tag_mc_end:
1225     \tag_struct_end:
1226         \tag_mc_begin:n {}
1227             \ (#3)
1228         \tag_mc_end:
1229     \group_end:
1230     \tag_struct_end:
1231     \tagpdfparaOn
1232     \__block_start_para_structure_unconditionally:n { \PARALABEL }
1233     \itshape
1234     \hskip\labelsep
1235     \ignorespaces
1236 }
1237 \def\@endtheorem{\endblockenv}

```

(End of definition for `\@begintheorem` and `\@opargbegintheorem`. These functions are documented on page 11.)

8 Instance declarations for environments

8.1 Blockenv instances

The blockenv instances handle overall setup for the document-level environments, i.e.,

- name of the environment for debugging purposes (`env-name`)
- how tagging should be performed (`tagging-recipe`, `tag-name`, `tag-class`)
- does this environment changes the block level if nested (`level-increase`)
- any special setup code; normally not used (`setup-code`)
- what kind of block instance should be used (`block-instance`)
- what kind of para instance should be used; empty means inherit from the outside (`para-instance`)
- are inner paragraphs real paragraphs (default) or are they just `<text>` structures and part of an outer paragraph (`para-flattened`)
- what kind of inner instance should be used, if any (`inner-instance`, `inner-instance-type`)
- the counter name of the inner level, if any (`inner-level-counter`)
- supported nesting depth of the inner level, if relevant (`max-inner-levels`)
- extra code executed at the end, by default `\ignorespaces` (`final-code`)

The blockenv `displayblock` instance below shows the full set with those using default values being commented out.

8.1.1 Basic instances

blockenv displayblock (*inst.*)
should this really generate
a /Figure structure?

This is like LATEX 2 ε 's `trivlist`, i.e., it produces a vertical block with default setting, but doesn't put a list inside but uses a `<Figure>` structure.

```
1238 \DeclareInstance{blockenv}{displayblock}{display}
1239 {
1240   env-name      = displayblock,
1241   % tagging-recipe = standard,
1242   % tag-name      = ,
1243   % tag-class     = ,
1244   level-increase = false,
1245   % setup-code    = ,
1246   % block-instance = displayblock ,
1247   % para-instance  = ,
1248   % para-flattened = false ,
1249   % inner-instance = ,
1250   % inner-instance-type = list , % not relevant as there is no inner instance
1251   % inner-level-counter = ,      % not relevant as there is no inner instance
1252   % max-inner-levels = 4,       % not relevant as there is no inner instance
1253   % final-code = \ignorespaces ,
1254 }
```

nv displayblockflattened (*inst.*) This flattens inner paragraphs without any surrounding tag structure by using the `basic` tagging recipe.

```
1255 \DeclareInstance{blockenv}{displayblockflattened}{display}
1256 {
1257   env-name      = displayblockflattened,
1258   tag-name      = ,
1259   tag-class     = ,
1260   tagging-recipe = basic,
1261   inner-level-counter = ,
1262   level-increase = false,
1263   setup-code    = ,
1264   block-instance = displayblock ,
1265   para-flattened = true ,
1266   inner-instance = ,
1267 }
```

8.1.2 Center, flushleft, and flushright instances

All three environments use the `displayblock` instance as block instance. They only differ in the choice of para instance.

blockenv center (*inst.*) The `center` environment without using a list internally.

```
1268 \DeclareInstance{blockenv}{center}{display}
1269 {
1270   env-name      = center,
1271   tag-name      = ,
1272   tag-class     = ,
1273   tagging-recipe = basic,
1274   inner-level-counter = ,
1275   level-increase = false,
1276   setup-code    = ,
1277   block-instance = displayblock ,
```

```

1278     para-flattened = true ,
1279     para-instance = center ,
1280     inner-instance = ,
1281 }

```

blockenv flushleft (*inst.*) The **flushleft** environment without using a list internally.

```

1282 \DeclareInstance{blockenv}{flushleft}{display}
1283 {
1284     env-name      = flushleft,
1285     tag-name      = ,
1286     tag-class     = ,
1287     tagging-recipe = basic,
1288     inner-level-counter = ,
1289     level-increase = false,
1290     setup-code    = ,
1291     block-instance = displayblock ,
1292     para-flattened = true ,
1293     para-instance  = raggedright ,
1294     inner-instance = ,
1295 }

```

blockenv flushright (*inst.*) The **flushright** environment without using a list internally.

```

1296 \DeclareInstance{blockenv}{flushright}{display}
1297 {
1298     env-name      = flushleft,
1299     tag-name      = ,
1300     tag-class     = ,
1301     tagging-recipe = basic,
1302     inner-level-counter = ,
1303     level-increase = false,
1304     setup-code    = ,
1305     block-instance = displayblock ,
1306     para-flattened = true ,
1307     para-instance  = raggedleft ,
1308     inner-instance = ,
1309 }

```

8.1.3 Blockquote instances

LATEX 2_E has two environments for quoting: **quote** and **quoation**. By default they differ only in indentation of inner paragraphs. This is handled by using separate block instances.

The tag names are both roll-mapped to <BlockQuote>.

blockenv quotation (*inst.*) For the **quotation** environment:

```

1310 \DeclareInstance{blockenv}{quotation}{display}
1311 {
1312     env-name      = quotation,
1313     tag-name      = quotation,
1314     tag-class     = ,
1315     tagging-recipe = standard,
1316     inner-level-counter = ,
1317     level-increase = true,
1318     setup-code    = ,

```

```

1319   block-instance = quotationblock ,
1320   inner-instance = ,
1321 }
```

blockenv quote (*inst.*) For the quote environment:

```

1322 \DeclareInstance{blockenv}{quote}{display}
1323 {
1324   env-name      = quote,
1325   tag-name      = quote,
1326   tag-class     = ,
1327   tagging-recipe = standard,
1328   inner-level-counter = ,
1329   level-increase = true,
1330   setup-code    = ,
1331   block-instance = quoteblock ,
1332   inner-instance = ,
1333 }
```

8.1.4 The theorem instance

blockenv theorem (*inst.*) We use <theorem-like> as the structure name and rolemap it to a <Sect> because that can hold a <Caption>.

```

1334 \DeclareInstance{blockenv}{theorem}{display}
1335 {
1336   env-name      = theorem-like,
1337   tag-name      = theorem-like,
1338   tag-class     = ,
1339   tagging-recipe = standalone,
1340   inner-level-counter = ,
1341   level-increase = false,
1342   setup-code    = ,
1343   block-instance = theoremblock ,
1344 }
```

8.1.5 The verbatim instance

blockenv verbatim (*inst.*) The rolemapping is <verbatim> to <Code> and <codeline> to <Sub> (which is role mapped to in pdf 1.7). Sub inside Code is allowed according the errata of ISO 32005. The paragraphs inside verbatim are flattened. Line numbers should inside the <codeline> structure and be tagged either as <Lbl> or <Artifact><Lbl>.

```

1345 \DeclareInstance{blockenv}{verbatim}{display}
1346 {
1347   env-name      = verbatim,
1348   tag-name      = verbatim,
1349   tag-class     = ,
1350   tagging-recipe = standard,
1351   para-flattened = true,
1352   inner-level-counter = ,
1353   level-increase = false,
1354   setup-code    = ,
1355   block-instance = verbatimblock ,
1356   inner-instance = ,
1357   final-code    = \legacyverbatimsetup ,
```

```

1358     para-instance = justify
1359 }
```

8.1.6 Standard list instances

blockenv itemize (*inst.*) For the **itemize** environment:

```

1360 \DeclareInstance{blockenv}{itemize}{display}
1361 {
1362   env-name      = itemize,
1363   tag-name      = itemize,
1364   tag-class     = itemize,
1365   tagging-recipe = list,
1366   inner-level-counter = \citemdepth,
1367   level-increase = true,
1368   max-inner-levels = 4,
1369   setup-code    = ,
1370   block-instance = list ,
1371   inner-instance = itemize ,
1372 }
```

blockenv enumerate (*inst.*) For the **enumerate** environment:

```

1373 \DeclareInstance{blockenv}{enumerate}{display}
1374 {
1375   env-name      = enumerate,
1376   tag-name      = enumerate,
1377   tag-class     = enumerate,
1378   tagging-recipe = list,
1379   level-increase = true,
1380   setup-code    = ,
1381   block-instance = list ,
1382   inner-level-counter = \cenumdepth,
1383   max-inner-levels = 4,
1384   inner-instance = enum ,
1385 }
```

blockenv description (*inst.*) For the **description** environment:

```

1386
1387 \DeclareInstance{blockenv}{description}{display}
1388 {
1389   env-name      = description,
1390   tag-name      = description,
1391   tag-class     = description,
1392   tagging-recipe = list,
1393   inner-level-counter = ,
1394   level-increase = true,
1395   setup-code    = ,
1396   block-instance = list ,
1397   inner-instance = description ,
1398 }
```

blockenv list (*inst.*) The general (legacy) **list** environment does some of its setup in the **setup-code** key.

```

1399 \DeclareInstance{blockenv}{list}{display}
1400 {
```

```

1401 env-name      = list,
1402 tag-name       = list,
1403 tag-class      = ,
1404 tagging-recipe = list,
1405 level-increase = true,
1406 setup-code     = \legacylistsetupcode ,
1407 block-instance = list ,
1408 inner-level-counter = ,
1409 inner-instance = legacy ,
1410 }

```

8.2 Block instances

Below, we declare the different block instances for the document-level environments. Some, such as the displayblock ones are shared between different environments (as long as one doesn't need to adjust individual values), other environments have their own instances (for precisely that reason).

8.2.1 Displayblock instances

We provide 6 nesting levels (as in L^AT_EX 2 _{ε}). If you want to provide more you need to change the `maxblocklevels` counter, offer further `displayblock-xx` instances but also define further (legacy) `\list{romannumeral}` commands for the defaults. If not, then the settings from the previous level are reused automatically—which may or may not be good enough).

```

1411 \setcounter{maxblocklevels}{6}

block displayblock-0 (inst.) Here we need level zero as well in case a flattened displayblock (like the center env) it is
block displayblock-1 (inst.) used on top-level.
block displayblock-2 (inst.) We show all keys here for reference, with those using their default values commented
block displayblock-3 (inst.) out:
block displayblock-4 (inst.) 1412 \DeclareInstance{block}{displayblock-0}{display}
block displayblock-5 (inst.) 1413 {
block displayblock-6 (inst.) 1414 %   heading      = ,                                %??
1415 %   beginsep     = \topsep ,
1416 %   begin-par-skip = \partopsep ,
1417 %   par-skip      = \parsep ,
1418 %   end-skip      = \KeyValue{beginsep} ,
1419 %   end-par-skip  = \KeyValue{begin-par-skip} ,
1420 %   item-skip     = \itemsep ,
1421 %   beginpenalty  = \UserName{@beginparpenalty} ,
1422 %   endpenalty    = \UserName{@endparpenalty} ,
1423   leftmargin    = Opt ,
1424 %   rightmargin   = \rightmargin ,
1425 %   parindent     = Opt ,
1426 }

1427 \DeclareInstanceCopy{block}{displayblock-1}{displayblock-0}
1428 \DeclareInstanceCopy{block}{displayblock-2}{displayblock-0}
1429 \DeclareInstanceCopy{block}{displayblock-3}{displayblock-0}
1430 \DeclareInstanceCopy{block}{displayblock-4}{displayblock-0}
1431 \DeclareInstanceCopy{block}{displayblock-5}{displayblock-0}
1432 \DeclareInstanceCopy{block}{displayblock-6}{displayblock-0}

```

8.2.2 Verbatim instances

Verbatim instances have their own levels so that one can specify specific indentations or vertical separations between lines.

```

block verbatimblock-0 (inst.)
block verbatimblock-1 (inst.) 1433 \DeclareInstance{block}{verbatimblock-0}{display}
block verbatimblock-2 (inst.) 1434 {
block verbatimblock-3 (inst.) 1435     leftmargin      = Opt ,
block verbatimblock-4 (inst.) 1436     par-skip        = Opt ,
block verbatimblock-5 (inst.) 1437 }
block verbatimblock-6 (inst.) 1438 \DeclareInstanceCopy{block}{verbatimblock-1}{verbatimblock-0}
1439 \DeclareInstanceCopy{block}{verbatimblock-2}{verbatimblock-0}
1440 \DeclareInstanceCopy{block}{verbatimblock-3}{verbatimblock-0}
1441 \DeclareInstanceCopy{block}{verbatimblock-4}{verbatimblock-0}
1442 \DeclareInstanceCopy{block}{verbatimblock-5}{verbatimblock-0}
1443 \DeclareInstanceCopy{block}{verbatimblock-6}{verbatimblock-0}

```

8.2.3 Quote/quotationblock instances

Quote and quotation are not flattened, i.e., they change levels, thus they start with level 1 not 0.

```

block quoteblock-1 (inst.) Default layout is to indent equally from both sides.
block quoteblock-2 (inst.) 1444 \DeclareInstance{block}{quoteblock-1}{display}
block quoteblock-3 (inst.) 1445 { rightmargin = \KeyValue{leftmargin} }
block quoteblock-4 (inst.) 1446 \DeclareInstanceCopy{block}{quoteblock-2}{quoteblock-1}
block quoteblock-5 (inst.) 1447 \DeclareInstanceCopy{block}{quoteblock-3}{quoteblock-1}
block quoteblock-6 (inst.) 1448 \DeclareInstanceCopy{block}{quoteblock-4}{quoteblock-1}
1449 \DeclareInstanceCopy{block}{quoteblock-5}{quoteblock-1}
1450 \DeclareInstanceCopy{block}{quoteblock-6}{quoteblock-1}

block quotationblock-1 (inst.) Quotation additionally changes the parindent.
block quotationblock-2 (inst.) 1451 \DeclareInstance{block}{quotationblock-1}{display}
block quotationblock-3 (inst.) 1452 { parindent = 1.5em , rightmargin = \KeyValue{leftmargin} }
block quotationblock-4 (inst.) 1453 \DeclareInstanceCopy{block}{quotationblock-2}{quotationblock-1}
block quotationblock-5 (inst.) 1454 \DeclareInstanceCopy{block}{quotationblock-3}{quotationblock-1}
block quotationblock-6 (inst.) 1455 \DeclareInstanceCopy{block}{quotationblock-4}{quotationblock-1}
1456 \DeclareInstanceCopy{block}{quotationblock-5}{quotationblock-1}
1457 \DeclareInstanceCopy{block}{quotationblock-6}{quotationblock-1}

```

8.2.4 Block instances for the theorems

block theoremblock-0 (inst.) Theorems do not support nesting, so we have only one to set up. The L^AT_EX default reused the general value of \parindent and \parskip and, of course, they start at the outer margin.

```

1458 \DeclareInstance{block}{theoremblock-0}{display}
1459 {
1460     leftmargin      = Opt ,
1461     parindent       = \parindent ,
1462     par-skip        = \parskip ,
1463 }

```

8.2.5 Block instances for the standard lists

block list-1 (inst.) The block instances for the various list environments use the same underlying instance
block list-2 (inst.) (well, by default) and nothing needs to be set up specifically (because that is already
block list-3 (inst.) done in the legacy `\list<romannumeral>` unless a different layout is wanted.

```

block list-4 (inst.) 1464 \DeclareInstance{block}{list-1}{display}{

block list-5 (inst.) 1465 % heading      = ,           % unused, might vanish
block list-6 (inst.) 1466 % beginsep     = \topsep ,
1467 % begin-par-skip = \partopsep ,
1468 % par-skip       = \parsep ,
1469 % end-skip        = \KeyValue{beginsep} ,
1470 % end-par-skip   = \KeyValue{begin-par-skip} ,
1471 % beginpenalty   = \UserName{@beginparpenalty} ,
1472 % endpenalty     = \UserName{@endparpenalty} ,
1473 % leftmargin     = \leftmargin ,
1474 % rightmargin    = \rightmargin ,
1475 % parindent      = Opt ,
1476 }

1477 \DeclareInstance{block}{list-2}{display}{}
1478 \DeclareInstance{block}{list-3}{display}{}
1479 \DeclareInstance{block}{list-4}{display}{}
1480 \DeclareInstance{block}{list-5}{display}{}
1481 \DeclareInstance{block}{list-6}{display}{}

```

8.3 List instances for the standard lists

For all list instances we have to say what kind of label we want (`item-label`) and how it should be formatted.

list itemize-1 (inst.) For `itemize` environments this is all we need to do and we refer back to the external
list itemize-2 (inst.) definitions rather than defining the `item-label` code in the instance to ensure that old
list itemize-3 (inst.) documents still work.

```

list itemize-4 (inst.) 1482 \DeclareInstance{list}{itemize-1}{std}{ item-label = \labelitemi }
1483 \DeclareInstance{list}{itemize-2}{std}{ item-label = \labelitemii }
1484 \DeclareInstance{list}{itemize-3}{std}{ item-label = \labelitemiii }
1485 \DeclareInstance{list}{itemize-4}{std}{ item-label = \labelitemiv }

```

list enumerate-1 (inst.) `enumerate` environments are similar, except that we also have to say which counter to
list enumerate-2 (inst.) use on each level.

```

list enumerate-3 (inst.) 1486 \DeclareInstance{list}{enum-1}{std}
list enumerate-4 (inst.) 1487 { item-label = \labelenumi , counter = enumi }
1488 \DeclareInstance{list}{enum-2}{std}
1489 { item-label = \labelenumii , counter = enumii }
1490 \DeclareInstance{list}{enum-3}{std}
1491 { item-label = \labelenumiii , counter = enumiii }
1492 \DeclareInstance{list}{enum-4}{std}
1493 { item-label = \labelenumiv , counter = enumiv }

```

list legacy (inst.) For the legacy `list` environment there is only one instance which is reused on all levels.
This is done this way one because the legacy `list` environment sets all its parameters through its arguments. So this instances shouldn't really be touched. It sets the `legacy-support` key to true, which means that the list code uses `\makelabel` for formatting the label

```

1494 \DeclareInstance{list}{legacy}{std} {
1495   item-instance = basic ,
1496   legacy-support = true ,
1497 }

```

list description (inst.) The **description** lists also use only a single list instance with only one key not using the default:

```
1498 \DeclareInstance{list}{description}{std} { item-instance = description }
```

8.4 Item instances

item basic (inst.) There two item instances set up: **description** for use with the **description** environment **item description (inst.)** and **basic** for use with all other lists (up to now).

```

1499 \DeclareInstance{item}{basic}{std}
1500   { label-align = right }

1501 \DeclareInstance{item}{description}{std}
1502   {
1503     label-format = \normalfont\bfseries #1 ,
1504     label-align = left
1505   }

```

8.5 Para instances

```

1506 \tag_if_active:T
1507 {
1508   \tagpdfsetup
1509   {
1510     role/new-attribute = {justify}    {/0 /Layout /TextAlign/Justify},
1511     role/new-attribute = {center}     {/0 /Layout /TextAlign/Center},
1512     role/new-attribute = {raggedright}{/0 /Layout /TextAlign/Start},
1513     role/new-attribute = {raggedleft} {/0 /Layout /TextAlign/End},
1514   }
1515 }

```

para center (inst.)

```

1516 \DeclareInstance{para}{center}{std}
1517 {
1518   para-class      = center ,
1519   indent-width    = 0pt ,
1520 % start-skip      = 0pt ,
1521   left-skip       = \flushglue ,
1522   right-skip      = \flushglue ,
1523   end-skip        = \zskip ,
1524   final-hyphen-demerits = 0 ,
1525   cr-cmd          = \centercr ,
1526 }

```

para raggedright (inst.)

```

1527 \DeclareInstance{para}{raggedright}{std}
1528 {
1529   para-class      = raggedright ,
1530   indent-width    = 0pt ,
1531 % start-skip      = 0pt ,

```

```

1532   left-skip          = \z@skip ,
1533   right-skip         = \@flushglue ,
1534   end-skip           = \z@skip ,
1535   final-hyphen-demerits = 0 ,
1536   cr-cmd             = \@centercr ,
1537 }

```

`para raggedleft (inst.)`

```

1538 \DeclareInstance{para}{raggedleft}{std}
1539 {
1540   para-class          = raggedleft ,
1541   indent-width        = 0pt ,
1542 % start-skip         = 0pt ,
1543   left-skip           = \@flushglue ,
1544   right-skip          = \z@skip ,
1545   end-skip            = \z@skip ,
1546   final-hyphen-demerits = 0 ,
1547   cr-cmd              = \@centercr ,
1548 }

```

`para justify (inst.)` Justifying is exactly what the default values do, so the instance hasn't any special setup.

```

1549 \DeclareInstance{para}{justify}{std}
1550 {
1551 % para-class          = justify ,
1552 % indent-width        = \parindent ,
1553 % start-skip          = 0pt ,
1554 % left-skip           = \z@skip ,
1555 % right-skip          = \z@skip ,
1556 % end-skip            = \@flushglue ,
1557 % final-hyphen-demerits = 5000 ,
1558 % cr-cmd              = \@normalcr ,
1559 }

\centering
\raggedleft \DeclareRobustCommand\centering {\UseInstance{para}{center}{}}
\raggedright \DeclareRobustCommand\raggedleft {\UseInstance{para}{raggedleft}{}}
\justifying \DeclareRobustCommand\raggedright{\UseInstance{para}{raggedright}{}}
\justifying \DeclareRobustCommand\justifying {\UseInstance{para}{justify}{}}
```

(End of definition for `\centering` and others.)

```

1565 </package>
1566 <!*latex-lab>
1567 \ProvidesFile{block-latex-lab-testphase.ltx}
1568   [!ltlabblockdate\space v\ltlabblockversion\space
1569    blockenv implementation]
1570 \RequirePackage{latex-lab-testphase-block}
1571 </!*latex-lab>
```

A Documentation from first prototype implementations

A.1 Open questions

- Existing questions — moved to issues —

A.2 Code cleanup

- Actually implement what's announced.
- Encapsulate most uses of `\legacy_if...` into commands with `expl3` syntax: we cannot rename these booleans for compatibility reasons but we can make the code cleaner nevertheless. — made issue —
- The `\topsep` and `\partopsep` business is tricky to reproduce exactly (see `\@topsepadd` and `\@topsep`) because of how it accumulates when lists are nested immediately.

A.3 Tasks

- Change author to LaTeX Team once it's nice enough to deserve that label.
- Reproducing exactly the standard layouts and examples in the `enumitem` documentation.
- Hooks, but do not duplicate those that already exist as environment hooks. Hence, mostly around items.
- Customization and interaction with LDB:
 - Allow arbitrary nesting depth with automatically defined styles for labels, counters etc.
 - Adapt everything to font size! (e.g. footnotes).
 - How to model the inheritance from trivlist to list to enumerate?
- Add key-value settings mimicking `enumitem`'s ability to set any four of five horizontal parameters and deduce the fifth by $\leftmargin + \itemindent = \labelindent + \labelwidth + \labelsep$.
- Provide good ways to customize how overlong labels are dealt with.
- Use the `.aux` file.
 - Implement the `\ref` styles that `enumitem` provides.
 - Reverse enumerations, important in publication lists and the like. Somehow avoid needing 3 compilations for references to reverse enumerations to settle?
 - Ability to calculate `\labelwidth` from the label contents. Share calculated parameters between multiple environments (cf. `resume` option).
- Related to grabbing the whole list environment, and input syntax variations:

- Other layouts: tabular (see `listliketab` vs `typed-checklist`), multicolumn and horizontally numbered (see `tasks`), inline lists, runin lists in the easy case where there is no intervening `\par`.
- Formatting the item text in a box or similar (requires grabbing the whole list).
- Filtering which items to show: hide certain items according to criteria (useful together with list reuse), see `typed-checklist`.
- Shorthands `\iitem` for automatic nested lists, or `\1`, `\2` etc from `outlines`.
- Support markdown input like `asciilist`.
- Check interaction with `babel` options such as `french` or `accadian` (see FrenchItemizeSpacing)
- RTL and vertical typesetting.

B Plan of attack of first prototype

Typesetting list environments involves a rather large number of parameters. They can be affected by the context such as the total list nesting level, the nesting level of the given type of list, and the font size. An environment like `enumerate` has two main aspects.

- It has a certain layout in the page, with vertical and horizontal spacing around it. This type of layout is shared with environments such as `quote`, `flushright`, or `tabbing`. This common layout is implemented in L^AT_EX 2 _{ε} through `\trivlist` (or `\list`).
- It defines how each `\item` should be typeset: how to construct the label, in particular the `counter` name, and how to format the content of the item.

This suggests defining two object types, *block* and *item* covering these two aspects.¹ While the *item* type will perhaps have a single template, one could typeset a *block* object in several ways, for instance the standard L^AT_EX 2 _{ε} way or a fancy colored box.

The *general block* template should receive the following parameters. The *plain block* template is a restricted template that freezes all item-related parameters to dummy values (`counter`, `start`, `resume`, `label-width`, `label-sep` and all `item-*`). The *list block* template is a restricted template² that omits the `heading` parameter and whose default for `item-instance` is non-empty.

- Structural parameters: the `heading` to place before, `counter` name, `start` value, whether to `resume` a previous list, and the `item-instance` (an *item* instance) to use when typesetting items.
- Vertical spacing and penalties: `beginpenalty`, `beginsep`, `begin-par-skip`, `item-penalty`, `item-skip`, `item-par-skip`, `endpenalty`, `end-skip`, `end-par-skip`.
- Horizontal spacing: `rightmargin`, `leftmargin`, `parindent`, `item-indent`, `label-width`, `label-sep`.

A document class should edit these templates (or define restricted templates) to set up default values that depend on `\g_block_nesting_depth_int`, namely how many lists are nested overall.³ The document class should then set up an instance of these templates for each environment, with appropriate settings such as a `heading`, a suitable `item-instance`, or making `margin-right` equal to `margin-left` in a `quote` environment.

The `inline-list block` template receives many fewer parameters. Note that `beginsep`, `item-skip`, `end-skip` are now *horizontal* skips.

- Structural parameters: `counter`, `start`, `resume`, `item-instance`.
- Spacing and penalties: `beginpenalty`, `beginsep`, `item-penalty`, `item-skip`, `endpenalty`, `end-skip`.
- Horizontal spacing: `label-width`, `label-sep`.

The `std item` template should receive the following parameters. They depend on the type of list and its nesting level among lists of such type, but typically not on the total nesting level.

- Counter name (`counter`), shared with the parent `list block` template, but needed for incrementing.
- Label construction: a function `counter-label` that produces the label from the counter name, used if `\item` is given without argument.
- References: a function `counter-ref` for how the label should be referred to when it is constructed from the counter, `label-ref` and `label-autoref` used when `\item` has an optional argument.
- Label formatting: `label-format` function, `label-strut` boolean.
- Label alignment (`label-align`, `label-boxed`, `next-line`).
- Content parameters: `text-font`.
- A `compatibility` boolean that controls for instance whether `\makelabel` is used.

The document class should set up an instance such as `enumiii` for each environment and nesting level.⁴

A given environment will adjust some nesting levels, then call the `block` instance appropriate to the environment type, passing it the `item` instance appropriate to the environment and depth. Additional context-dependence could be provided by `I3lDb`, but the main context-dependence should not rely on it for simplicity reasons and incidentally because `I3lDb` is not yet available.

¹Possibly also `endblock` to deal with decorations at the end?

²A better approach could be to have a notion of inheritance for object types, so that we end up with two different *object types*. Then we can implement other template for the list object type: `table` for lists typeset as rows/columns of a table, `inline` for lists typeset in horizontal mode within a paragraph, and `runin` for run-in lists.

³Does `xtemplate` provide a way to specify default values that are only evaluated once an instance is used?

⁴This should be made easily extendible to deeper levels.

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\`	292, 488, 489, 1090
\`	711, 1195, 1219, 1227
Numbers	
\`1	62
\`2	62
A	
\addpenalty	266, 387, 677
\AddToHook	614, 646, 739, 796, 1018, 1029, 1037, 1076, 1087, 1104, 1133
\addvspace	267, 385, 388, 389, 678
\arabic	103
B	
\begin	12, 839
\begingroup	848
\bfseries	1193, 1217, 1503
block (objecttype)	36
block commands:	
\block_debug_off:	11, 123, 128, 141
\block_debug_on:	11, 123, 123, 140
\g_block_nesting_depth_int	11, 143, 186, 190, 192, 202, 205, 244
block display (template)	58, 299
block displayblock-0 (instance)	1412
block displayblock-1 (instance)	1412
block displayblock-2 (instance)	1412
block displayblock-3 (instance)	1412
block displayblock-4 (instance)	1412
block displayblock-5 (instance)	1412
block displayblock-6 (instance)	1412
block internal commands:	
\block_beginpar_hmode:N	
.	704, 704, 961, 983, 997
\block_beginpar_vmode:	
.	683, 683, 963, 985, 999
\l_block_block_instance_tl	
.	153, 202, 204, 273
\l_block_botsep_skip	305, 499
\l_block_counter_label:n	507, 544
\l_block_counter_ref:n	508
\l_block_counter_start_int	
.	424, 463, 473
\l_block_counter_tl	422, 456, 469
\l_block_debug:n	121, 121, 135
\g_block_debug_bool	
.	120, 125, 130, 136, 138
\l_block_debug_gset:	123, 126, 131, 133
\l_block_debug_typeout:n	121,
122, 137, 163, 201, 210, 216, 242,	
256, 275, 400, 404, 408, 436, 482,	
525, 547, 617, 684, 708, 722, 729,	
748, 765, 786, 801, 874, 878, 938, 949	
\l_block_effective_top_skip	
.	338, 340, 388, 644
\l_block_env_name_tl	147, 163, 450
\l_block_evaluate_saved_user_- keys:nn	25, 26, 29, 413, 413, 416, 417, 439, 442, 527
\l_block_final_code_tl	19, 160, 232
\l_block_heading_tl	301, 316, 318
\l_block_if_list:TF	250, 255, 272, 272
\l_block_inner_begin:	
.	870, 870, 973, 986
\l_block_inner_end:	873, 873, 974, 987
\l_block_inner_instance_tl	
.	159, 214, 216, 220
\l_block_inner_instance_type_tl	158, 219
\l_block_inner_level_counter_tl	156, 177, 179, 182, 217, 218, 221, 223
\l_block_inter_item:	33, 661, 670, 670
\l_block_item_align_tl	
.	518, 519, 520, 562, 566, 591
\l_block_item_compatibility_- bool	516, 538
\l_block_item_everypar:	28, 31–33, 481, 589, 613, 613, 614, 636
\l_block_item_everypar_first:	
.	481, 613, 639
\l_block_item_everypar_std:	
.	589, 613, 616
\l_block_item_instance:n	
.	33, 426, 650, 663, 664
\l_block_item_label_tl	423, 476, 478
\l_block_item_parsep_skip	586
\l_block_label_autoref:n	510
\l_block_label_boxed_bool	513, 551
\l_block_label_format:n	
.	31, 511, 595, 600
\l_block_label_given_tl	
.	29, 504, 526, 535, 548
\l_block_label_ref:n	509
\l_block_label_strut_bool	512, 602

\g_block_labels_box	29, 31, 369, 372, 575, 577, 592, 625
\l_block_legacy_env_params_tl	48, 1107, 1123, 1132
\l_block_legacy_support_bool	433, 603
\l_block_level_incr_bool	151, 184, 243
_block_list_begin: ..	903, 903, 1000
_block_list_end: ..	942, 942, 1001
_block_list_item_begin:	910, 910, 1002
_block_list_item_end: ..	933, 933, 1003
\l_block_long_label_bool	573, 574, 582, 594
_block_make_label_box:n	29, 541, 543, 548, 595, 595
\l_block_max_inner_levels_tl	157, 180
\l_block_next_line_bool ..	514, 581
\l_block_one_label_box	31, 554, 558, 560, 564, 565, 569, 570, 572, 579, 592, 597
\l_block_para_instance_tl	154, 208, 211, 212
\l_block_parbotsep_skip ..	306, 500
\l_block_parindent_dim ..	312, 361
_block_recipe_basic:	959, 959
_block_recipe_list:	994, 994
_block_recipe_standalone:	968, 968
_block_recipe_standard: ..	980, 980
\l_block_resume_bool ..	425, 460, 470
_block_save_user_keys:n	414
\l_block_setup_code_tl ..	18, 152, 200
_block_skip_remove_last:	115, 118, 252, 327, 673, 674
_block_skip_set_to_last:N	115, 115, 260, 377
_block_start_para_structure:n	743, 747, 747
_block_start_para_structure_-unconditionally:n	774, 867, 957, 1205, 1232
\l_block_tag_class_tl ..	149, 1008, 1010
\l_block_tag_inner_tag_tl	871, 977, 978, 990, 991, 993
\l_block_tag_name_tl	148, 976, 978, 989, 991, 1005, 1007
\l_block_tagging_recipe_tl	150, 196
\l_block_text_font_tl	515
\l_block_thm_current_counter_tl	1180, 1183, 1190, 1214
\l_block_tmpa_skip ..	377, 378, 379, 643
\l_block_topsepadd_skip	21, 267, 320, 323, 338, 644
\l_block_unused_blockenv_keys_tl	19, 207, 225, 226, 228, 234
block list-1 (instance)	1464
block list-2 (instance)	1464
block list-3 (instance)	1464
block list-4 (instance)	1464
block list-5 (instance)	1464
block list-6 (instance)	1464
block quotationblock-1 (instance) ..	1451
block quotationblock-2 (instance) ..	1451
block quotationblock-3 (instance) ..	1451
block quotationblock-4 (instance) ..	1451
block quotationblock-5 (instance) ..	1451
block quotationblock-6 (instance) ..	1451
block quoteblock-1 (instance)	1444
block quoteblock-2 (instance)	1444
block quoteblock-3 (instance)	1444
block quoteblock-4 (instance)	1444
block quoteblock-5 (instance)	1444
block quoteblock-6 (instance)	1444
block theoremblock-0 (instance)	1458
block verbatimblock-0 (instance) ..	1433
block verbatimblock-1 (instance) ..	1433
block verbatimblock-2 (instance) ..	1433
block verbatimblock-3 (instance) ..	1433
block verbatimblock-4 (instance) ..	1433
block verbatimblock-5 (instance) ..	1433
block verbatimblock-6 (instance) ..	1433
blockenv (objecttype)	36
blockenv center (instance)	1268
blockenv description (instance) ..	1386
blockenv display (template)	41, 145
blockenv displayblock (instance) ..	1238
blockenv displayblockflattened (instance)	1255
blockenv enumerate (instance)	1373
blockenv flushleft (instance)	1282
blockenv flushright (instance)	1296
blockenv itemize (instance)	1360
blockenv list (instance)	1399
blockenv quotation (instance)	1310
blockenv quote (instance)	1322
blockenv theorem (instance)	1334
blockenv verbatim (instance)	1345
blockpar internal commands:	
_blockpar	837
bool commands:	
\bool_gset_false:N	130
\bool_gset_true:N	125
\bool_if:NTF	136, 138, 171, 184, 243, 460, 470, 538, 581, 582,

\bool_if:nTF	549	
\bool_new:N	120, 594	
\bool_set_false:N	574	
\bool_set_true:N	573	
box commands:		
\box_if_empty:NTF	623	
\box_new:N	592, 593	
\box_use_drop:N	565, 570, 625	
\box_wd:N	554, 558, 572	
\break	582	
C		
center (env.)	1018	
\centering	1560	
\clubpenalty	18, 632, 635	
color commands:		
\color_select:n	711	
cs commands:		
\cs_generate_variant:Nn	119	
\cs_gset_protected:Npx	135, 137	
\cs_if_free:NTF	650	
\cs_new:Npn	143, 241, 272, 274, 399, 403, 407, 414, 639, 851, 870, 873, 957, 959, 968, 980, 994, 1116	
\cs_new_eq:NN	32, 118, 121, 122, 413, 611, 612, 613, 642, 680, 681	
\cs_new_protected:Npn	115, 123, 128, 133, 140, 141, 595, 616, 670, 747, 774	
\cs_set:Npe	26, 417, 442	
\cs_set:Npn	683, 704, 717, 864, 903, 910, 911, 925, 933, 942	
\cs_set_eq:NN	416, 439, 481, 589, 636, 836, 837, 838, 960, 962, 969, 971, 973, 974, 982, 984, 986, 987, 996, 998, 1000, 1001, 1002, 1003, 1139	
\cs_set_protected:Npn	813	
\csname	846, 1146, 1162	
D		
\DebugBlocksOff	11, 140	
\DebugBlocksOn	11, 140	
\DeclareHookRule	615	
\DeclareInstance	1238, 1255, 1268, 1282, 1296, 1310, 1322, 1334, 1345, 1360, 1373, 1387, 1399, 1412, 1433, 1444, 1451, 1458, 1464, 1477, 1478, 1479, 1480, 1481, 1482, 1483, 1484, 1485, 1486, 1488, 1490, 1492, 1494, 1498, 1499, 1501, 1516, 1527, 1538, 1549	
\DeclareInstanceCopy	1427, 1428, 1429, 1430, 1431, 1432, 1438, 1439, 1440, 1441,	
\endblockenv	241, 1014, 1017, 1021, 1024, 1027, 1032, 1035, 1043, 1049, 1079, 1082, 1085, 1102, 1114, 1142, 1237	
\endblockenv	11	
\endcsname	846, 1146, 1162	
\endgraf	838	
enumerate (env.)	1076	
environments:		
center	1018	
description	1076	
displayblock	1012	
displayblockflattened	1015	
enumerate	1076	
flushleft	1018	
flushright	1018	
itemize	1076	
list	1104	
quotation	1029	
quote	1029	
trivlist	1133	
verbatim	1037	
verbatim*	1037	
verse	1087	
\everypar	13, 21, 24, 25, 1064	

exp commands:	
\exp_after:wN	562, 566
\exp_not:n	26, 418, 444, 446
\expandafter	1064, 1146, 1162
\ExplSyntaxOn	7
F	
\fi	16, 29, 862, 1060, 1061
fi commands:	
\fii	823
\finalhyphendemerits	291
flushleft (env.)	1018
flushright (env.)	1018
\frenchspacing	1040, 1046
G	
\global	34, 35, 1176, 1177
group commands:	
\group_begin:	1192, 1216
\group_end:	1202, 1229
H	
hbox commands:	
\hbox_gset:Nn	369, 575
\hbox_set:Nn	569, 597
\hbox_set_to_wd:Nnn	560
\hbox_unpack_drop:N	372, 564, 577, 579
\hfil	582
hook commands:	
\hook_use:n	818, 825
Hooks:	
para/begin	31, 32
\hskip	1207, 1234
\hss	518, 519, 520
I	
if commands:	
\if_int_compare:w	821
\iffalse	34
\ifhmode	1060
\IfNoValueTF	1151
\iftrue	35
\ifvmode	852
\ignorespaces	56, 666, 1208, 1235, 1253
\indent	672
instances:	
block displayblock-0	1412
block displayblock-1	1412
block displayblock-2	1412
block displayblock-3	1412
block displayblock-4	1412
block displayblock-5	1412
block displayblock-6	1412
block list-1	1464
block list-2	1464
block list-3	1464
block list-4	1464
block list-5	1464
block list-6	1464
block quotationblock-1	1451
block quotationblock-2	1451
block quotationblock-3	1451
block quotationblock-4	1451
block quotationblock-5	1451
block quotationblock-6	1451
block quoteblock-1	1444
block quoteblock-2	1444
block quoteblock-3	1444
block quoteblock-4	1444
block quoteblock-5	1444
block quoteblock-6	1444
block theoremblock-0	1458
block verbatimblock-0	1433
block verbatimblock-1	1433
block verbatimblock-2	1433
block verbatimblock-3	1433
block verbatimblock-4	1433
block verbatimblock-5	1433
block verbatimblock-6	1433
blockenv center	1268
blockenv description	1386
blockenv displayblock	1238
blockenv displayblockflattened	1255
blockenv enumerate	1373
blockenv flushleft	1282
blockenv flushright	1296
blockenv itemize	1360
blockenv list	1399
blockenv quotation	1310
blockenv quote	1322
blockenv theorem	1334
blockenv verbatim	1345
item basic	1499
item description	1499
list description	1498
list enumerate-1	1486
list enumerate-2	1486
list enumerate-3	1486
list enumerate-4	1486
list itemize-1	1482
list itemize-2	1482
list itemize-3	1482
list itemize-4	1482
list legacy	1494
para center	1516
para justify	1549
para raggedleft	1538
para raggedright	1527

int commands:	
\int_compare:nNnTF	166, 179, 186, 350, 692
\int_gdecr:N	244
\int_gincr:N	190
\int_gset:Nn	462, 472
\int_if_exist:NTF	235
\int_incr:N	168, 173, 182, 349
\int_new:N	237
\int_set:Nn	632
\int_set_eq:NN	635
\int_to_roman:n	191
\int_use:N	202, 204, 218, 223, 711
\int_zero:N	344
\c_zero_int	627
\interlinepenalty	1057, 1060
item (objecttype)	36
\item	12, 29, 532, 646, 672, 914, 1100
item basic (instance)	1499
item description (instance)	1499
item std (template)	101, 503
\itemindent	96, 430, 578, 623, 1119
itemize (env.)	1076
\itemsep	66, 94, 307, 427, 496, 678, 1420
\itshape	1206, 1233
J	
\justifying	1560
K	
\kern	623
kernel internal commands:	
__kernel_displayblock_begin:	42, 365, 399, 399, 964, 973, 986, 1000
__kernel_displayblock_beginpar_hmode:w	328, 399, 403, 960, 969, 982, 996
__kernel_displayblock_beginpar_vmode:	324, 399, 407, 962, 971, 984, 998
__kernel_displayblock_doendpe:	36, 8, 19, 32, 717, 717
__kernel_displayblock_end:	42, 254, 274, 274, 965, 974, 987, 1001
__kernel_endpe_vmode:	832, 849, 851, 851
__kernel_list_item_begin:	658, 676, 680, 680, 1002
__kernel_list_item_end:	675, 680, 681, 1003
__kernel_list_label_after:	626, 642, 642, 864, 864
__kernel_list_label_begin:	599, 611, 611, 911, 911
__kernel_list_label_end:	608, 611, 612, 925, 925
keys commands:	
\keys_define:nn	28, 393, 493, 503
\KeyValue	64, 65, 104, 1418, 1419, 1445, 1452, 1469, 1470
L	
\labelenumi	1487
\labelenumii	1489
\labelenumiii	1491
\labelenumiv	1493
\labelitemi	1482
\labelitemii	1483
\labelitemiii	1484
\labelitemiv	1485
\labelsep	98, 432, 578, 580, 1207, 1234
\labelwidth	97, 431, 558, 560, 572, 578, 1138
\language	1053
\lastbox	24
\LBody	930, 932
\leavevmode	1057
\leftmargin	69, 311, 362, 363, 371, 373, 1096, 1097, 1137, 1473
\leftskip	287, 341
legacy commands:	
\legacy_if:nTF	245, 250, 257, 258, 319, 330, 336, 347, 366, 375, 384, 458, 620, 629, 640, 656, 671, 685, 687, 720, 741, 749, 751, 875, 934, 943, 945, 1124
\legacy_if_gset_false:n	248, 255, 619, 622, 631, 659, 689
\legacy_if_gset_true:n	22, 268, 480, 665
\legacy_if_set_false:n	199, 337, 368, 618, 1121
\legacy_if_set_true:n	332, 333
\legacylistsetupcode	11, 1116, 1406
\legacyverbatimsetup	11, 1051, 1357
\let	34, 35, 964, 965, 1062, 1090, 1122
\linewidth	362, 364, 552, 554
list (env.)	1104
list (objecttype)	36
\list	1135
list description (instance)	1498
list enumerate-1 (instance)	1486
list enumerate-2 (instance)	1486
list enumerate-3 (instance)	1486
list enumerate-4 (instance)	1486
list itemize-1 (instance)	1482
list itemize-2 (instance)	1482
list itemize-3 (instance)	1482
list itemize-4 (instance)	1482

list legacy (instance)	1494	
list std (template)	87, 420	
\listparindent	397, 587, 588, 1117	
\LItag	902, 910	
\ltlabbblockdate	4, 1568	
\ltlabbblockversion	4, 1568	
M		
\makelabel	604, 1122, 1139	
\MakeLinkTarget	541, 543, 1190, 1214	
math internal commands:		
__math_tag_dollardollar_-		
display_end:	13	
mode commands:		
\mode_if_horizontal:TF	251, 673, 815, 820	
\mode_if_inner:TF	816	
\mode_if_vertical:TF	321	
\mode_leave_vertical:	247, 317, 319	
msg commands:		
\msg_error:nnnn	449, 531, 828	
\msg_new:nnnn	484	
N		
\newcommand	1068	
\newcounter	239	
\NewDocumentEnvironment	1012, 1015	
\newif	33	
\newline	583	
\NewTemplateType	36, 37, 38, 39, 40	
\newtheorem	11, 1144	
\nobreak	582	
\nobreakspace	1073	
\noexpand	532, 1162	
\noindent	1189, 1213	
\normalfont	1503	
NOT commands:		
\NOT_IMPLEMENTED	521	
\null	1057	
O		
\obeylines	1063	
object types:		
block	36	
blockenv	36	
item	36	
list	36	
para	36	
off (plug)	21, 21, 278	
on (plug)	21, 21, 278	
P		
\par	13, 9, 22, 252, 328, 672, 674, 715, 836, 1055	
Q		
quotation (env.)	1029	
quote (env.)	1029	
R		
\raggedleft	1560	
\raggedright	1560	
\relax	518, 520, 1100	
\RemoveFromHook	738, 795	
\renewcommand	1072	
\RenewDocumentCommand	647, 1144	
\RenewDocumentEnvironment	1019, 1022, 1025, 1030, 1033, 1038, 1044, 1077, 1080, 1083, 1088, 1105, 1134	
\RequirePackage	6, 1570	
\rightmargin	70, 310, 362, 1118, 1424, 1474	
\rightskip	288, 297, 342	
\rlap	711	

S

scan commands:
 \scan_stop: 814
 \setbox 24
 \setcounter 240, 1411
 \SetKnownTemplateKeys
 165, 315, 418, 441, 443, 528
 \SetTemplateKeys 296
skip commands:
 \skip_add:Nn 323, 340
 \skip_eval:n 385
 \skip_horizontal:n 371, 373, 578, 580
 \skip_new:N 643, 644, 645
 \skip_set:Nn 116, 297, 320
 \skip_set_eq:NN
 338, 342, 343, 359, 360, 586
 \skip_vertical:n 14, 263, 264, 378, 379
 \skip_zero:N 341
 \l_tmpa_skip 260, 261, 263, 264
socket commands:
 \socket_assign_plug:nn
 282, 966, 975, 988, 1004
 \socket_new:nn 277
 \socket_new_plug:nnn 278, 280
 \socket_use:n 270
Sockets:
 tagsupport/block-endpe 277
\space 4, 450, 489, 730, 1568
str commands:
 \str_if_eq:nnTF 1148
 \string 652
 \strut 602

T

tag commands:
 \tag_if_active:TF
 195, 682, 888, 1069, 1506
 \tag_mc_begin:n 710, 772,
 793, 918, 1194, 1198, 1218, 1222, 1226
 \tag_mc_end: 706,
 712, 802, 1196, 1200, 1220, 1224, 1228
 \tag_struct_begin:n 695, 756,
 766, 778, 787, 1191, 1197, 1215, 1221
 \tag_struct_end: 714, 733,
 804, 808, 858, 1201, 1203, 1225, 1230
tag internal commands:
 __tag_block_flattened_level_-
 int 17, 166, 168, 173, 235, 692
 __tag_check_para_begin_show:nn ..
 771, 792
 __tag_check_para_end_show:nn .. 803
 __tag_gincr_para_begin_int: 764, 785
 __tag_gincr_para_end_int: . 707, 800

__tag_gincr_para_main_begin_-
 int: 694, 755, 777
__tag_gincr_para_main_end_int: ..
 732, 807, 857, 877, 936, 947
\l__tag_L_attr_class_tl 886,
 887, 907, 1009, 1010, 1125, 1127, 1128
\l__tag_L_tag_tl
 883, 884, 906, 1006, 1007
\g__tag_mode_lua_bool 1070
\l__tag_para_attr_class_tl
 293, 769, 790
\l__tag_para_bool
 718, 740, 798, 853, 865
\g__tag_para_end_int 711
\l__tag_para_flattened_bool
 155, 171, 724, 727, 753, 775, 805, 855
\l__tag_para_main_attr_class_tl ..
 698, 759, 781
__tag_para_main_store_struct: ..
 700, 761, 783
\l__tag_para_main_tag_tl
 697, 730, 758, 780
\l__tag_para_show_bool 709
 \l__tag_para_tag_tl .. 768, 789, 1065
\tagmcbegin 922
\tagmcend 926
\tagpdfparaOff 715, 1188, 1212
\tagpdfparaOn 715, 1204, 1231
\tagpdfsetup 890, 1508
\tagstructbegin .. 871, 904, 910, 921, 930
\tagstructend
 879, 881, 929, 937, 940, 948, 951, 953
tagsupport/block-endpe (socket) 277
templates:
 block display 58, 299
 blockenv display 41, 145
 item std 101, 503
 list std 87, 420
 para std 75, 283
TeX and L^AT_EX 2_< commands:
 \@par 1057, 1060
 \begin{par} 6, 308, 387
 \begin{theorem} 11, 50, 1186
 \begin{thorem} 50
 \centercr 1090, 1525, 1536, 1547
 \clubpenalty 18, 635
 \currenvir 253, 843
 \currenvline 844
 \definecounter 1150
 \doendpe 11, 12, 8
 \domathendpfalse 15, 28, 33
 \domathendptrue 33
 \eha 842
 \ehc 653

\endparpenalty 6, 266, 309
 \endpfalse 20, 26, 281, 860
 \endptrue 8, 279
 \endtheorem 1177, 1237
 \enumdepth 1382
 \execute@begin@hook 845
 \flushglue 6,
 82, 343, 1521, 1522, 1533, 1543, 1556
 \ifdefinable 1146
 \ifnextchar 1184
 \undefined 841, 1169
 \ignorefalse 847
 \inmatherr 253, 649
 \itemdepth 1366
 \itemlabel 12, 25, 27,
 197, 411, 478, 542, 916, 928, 1109, 1126
 \itempenalty 7, 429, 677
 \kernel@after@para@after 826
 \kernel@after@para@end 819
 \kernel@refstepcounter ... 537, 1182
 \labels 31
 \latex@error 652, 842
 \list... 5
 \listctr 25, 27, 198, 411,
 462, 469, 472, 537, 541, 543, 544, 1120
 \listdepth 5, 17, 143
 \listi 5
 \listii 5
 \listvi 5
 \makeother 1062
 \mklab 1122
 \namedef 1176, 1177
 \newctr 1159
 \nmbrlist 27
 \nmbrlisttrue 468
 \nocounterr 1170
 \noitemerr 28, 42, 250, 336, 351, 640
 \noligs 1063
 \normalcr 6, 85, 1558
 \opargbegintheorem 50, 1186
 \outerparskip 264, 359, 380, 385
 \restorepar 17
 \rightskip 297, 342
 \setpar 345
 \setupverbinspace
 11, 1040, 1068
 \setupverbvisiblespace 1046
 \sxverbatim 1047
 \tempswafalse 1054
 \tempswatrue 1059
 \thm 11, 49, 50, 1176, 1180
 \thmcnter 1155, 1164
 \thmcntersep 1163
 \toodeep 181, 188
 \topsep 33, 61
 \topsepadd 33, 61
 \totalleftmargin 46, 363, 364
 \vobeyspaces 1040, 1046
 \xobeysp 1073
 \xthm 1184
 \xverbatim 1041
 \ythm 1184
 \arabic 7
 \begin 12, 39
 \bfseries 50
 \bibitem 42
 \g_block_nesting_depth_int 63
 \c@maxblocklevels 12, 187, 239
 \end 12
 \endblockenv 44
 \everypar 33, 34
 \hyper@nopatch@thm 1185
 \if@domathendpe 11, 27, 33
 \ifendpe 852
 \iftempswa 1056
 \ignorespaces 5, 19, 51
 \iitem 62
 \item 12, 20, 21,
 23–26, 28, 29, 31, 33, 42, 44, 45, 62, 63
 \itemindent 47, 61
 \itemsep 6
 \l@nohyphenation 1053
 \labelindent 61
 \labelsep 7, 61
 \labelwidth 7, 29, 31, 61
 \leftmargin 6, 61
 \leftskip 46
 \legacylistsetupcode 47
 \list 48, 62
 \list<romannumeral> 56, 58
 \listparindent 22, 31
 \makelabel 7, 31, 48, 58, 63
 \newline 29
 \newtheorem 49
 \noitemerr 20
 \online
 242, 617, 686, 708, 726, 731, 750,
 765, 786, 801, 844, 874, 878, 938, 949
 \par 10,
 12, 13, 21, 23, 28, 34–36, 38, 43, 44, 62
 \par@deathcycles 344, 349, 350
 \parindent 6, 31, 57
 \parsep 6
 \parskip 24, 57
 \partopsep 6, 61
 \pdffakespace 46
 \ref 61
 \refstepcounter 49

\reserved@a	842, 843, 850	\tl_if_novalue:nTF	119, 535, 662
\rightmargin	6	\tl_new:N	234, 411, 412, 591, 883, 886, 993, 1132, 1180
\SetKnownTemplateKeys	25	\tl_set:Nn ..	518, 519, 520, 884, 887, 977, 990, 1006, 1009, 1065, 1107, 1109, 1120, 1125, 1127, 1128, 1183
\spacefactor	28	\tl_set_eq:NN	207, 226, 469, 478, 526, 978, 991, 1007, 1010
\strut	8, 31	\topsep	61, 302, 320, 395, 498, 501, 1415, 1466
\textbf	50	trivlist (env.)	1133
\topsep	6, 61	\typeout	12, 138
\trivlist	62		
\usecounter	27		
\UseInstance	33		
\verbatim@font	1063		
\z@	24		
\z@skip	1523, 1532, 1534, 1544, 1545, 1554, 1555		
tex commands:			U
\tex_hskip:D	822	\unpenalty	1064
\tex_lastnodetype:D	821	\UnusedTemplateKeys	18, 206, 207, 226, 444, 447, 451, 529, 533
\tex_lastskip:D	116	use commands:	
\tex_par:D	824, 833	\use:N	191, 196
\tex_parshape:D	364	\use:n	605, 1139
\tex_parskip:D	14	\use_i:nn	562
\tex_unskip:D	118, 817	\use_ii:nn	566
\textbf	318	\use_none:n	121, 122
\the	13, 1064	\use_none:nn	413, 416, 439
\tiny	711	\UseHook	840
tl commands:		\UseInstance	203, 212, 219, 1013, 1016, 1020, 1023, 1026, 1031, 1034, 1039, 1045, 1078, 1081, 1084, 1091, 1112, 1187, 1211, 1560, 1561, 1562, 1563
\c_novalue_tl	29, 526	\UserName	67, 68, 95, 1173, 1421, 1422, 1471, 1472
\tl_clear:N	197, 198		
\tl_gset:Nn	1153, 1160, 1172		
\tl_if_blank:nTF	316, 537		
\tl_if_empty:NTF	177, 208, 214, 217, 221, 228, 447, 456, 476, 529, 976, 989, 1005, 1008, 1126		V
\tl_if_empty:nTF	415, 438, 916, 928	verbatim (env.)	1037
\tl_if_eq:NnTF	273	verbatim* (env.)	1037
		verse (env.)	1087