

The latex-lab-mathintent code*

L^AT_EX Project

February 22, 2025

Abstract

Contents

1	Introduction	1
2	The Implementation	1
	2.1 File declaration	1
	2.2 Invisible ops	1
	2.3 Wrapper files for testphase key	2
	Index	2

1 Introduction

This file implements Experiments with the MathML4 `intent` feature. Initially to give readings for invisible times and function application.

2 The Implementation

```
1 <@=math>
```

```
2 <*kernel>
```

2.1 File declaration

```
3 \ProvidesFile{latex-lab-mathintent.ltx}
```

```
4 [2025-01-17 v0.1a intent experiments]
```

2.2 Invisible ops

```
5 \ExplSyntaxOn
```

```
6 \protected\def\invisibletimes{
```

```
7 \if_cs_exist:N\luamml_annotate:en
```

```
8 \luamml_annotate:en {
```

*

```

9   core = {[0] = 'mo', intent="times", "\^{}2062"},
10  }{
11  \latelua{}
12  }
13  \fi:
14  }

15  \protected\def\functionapplication{
16  \if_cs_exist:N\luamml_annotate:en
17  \luamml_annotate:en {
18  core = {[0] = 'mo', intent="applied_to", "\^{}2061"},
19  }{
20  \latelua{}
21  }
22  \fi:
23  }

24  \ExplSyntaxOff
25  </kernel>

```

2.3 Wrapper files for testphase key

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

D		I	
\def	6, 15	if commands:	
		\if_cs_exist:N	7, 16
		\invisibletimes	6
E		L	
\ExplSyntaxOff	24	\latelua	11, 20
\ExplSyntaxOn	5	luamml commands:	
		\luamml_annotate:nn	7, 8, 16, 17
F		P	
fi commands:		\protected	6, 15
\fi:	13, 22	\ProvidesFile	3
\functionapplication	15		